

LG 55UL3J-M 16/7 Digital Signage 55" ADS LED smart LFD monitor kék



55", 3840x2160, 16:9, 400cd/m2, 1300:1, 8ms, USB2.0, HDMI, fejhallgató kimenet, LAN, Wi-Fi, hangszóró, falra szerelhető (VESA), portré mód (pivot), 160W, FELÁRAS HÁZHOZZÁLLÍTÁS

Cikkszám: 55UL3J-M

Ár:

417 700 Ft

55UL3J-M  
UHD Standard Signage

Tech Spec

Panel

- Screen Size: 55"
- Panel Technology: ADS
- Back Light Type: Direct

- Aspect Ratio: 16:9
- Native Resolution: 3,840 x 2,160 (4K UHD)
- Refresh Rate: 60Hz
- Brightness (Typ.): 400 nit
- Contrast Ratio: 1,200:1
- Dynamic CR: 1,000,000 : 1
- Color gamut: DCI 80 %
- Viewing Angle (H x V): 178 × 178
- Color Depth: 1.07G (8bits + FRC)
- Response Time: 8ms (G to G)
- Surface Treatment: 1%
- Lifetime: 30,000Hrs (Min)
- Operation Hours (Hours / Days): 16 / 7
- Portrait / Landscape: Yes / Yes

**Mechanical Specification**

- Bezel Color: Ashed Blue
- Bezel Width: Off : 6.9/6.9/6.9/18.4 mm, On : 12.8/12.8/12.8/19.9 mm
- Weight (Head): 14.0 kg
- Packed Weight: 18.8 kg

- Monitor Dimensions (W × H × D): 1,235 x 715 x 57.5 mm
- 
- Carton Dimensions (W × H × D): 1,360 x 810 x 162 mm (Box outer size)
- 
- VESA™ Standard Mount Interface: 300 × 300 mm
- 

### **Key Feature**

- HW: Internal Memory (eMMC) 16 GB, Built-in Wi-Fi, Sensor (Temperature Sensor, Auto Brightness Sensor), Local Key Operation (Power On/Off Only)
- 
- SW: webOS 6.0, Embedded CMS (Local Contents Scheduling, Group Manager), USB Plug & Play, Fail Over, Background Image (Bootimg Logo Image, No Signal Image), Sync Mode (RS-232C Sync, Local Network Sync), Screen Share, Video Tag (4, Max One HDMI Input), Play via URL, Rotation (Screen Rotation, External Input Rotation), Gapless Playback, Tile Mode Setting, Setting Data Cloning, SNMP, ISM Method, Auto Set ID, Status Mailing, Control Manager, 3rd Party Compatibility (Cisco Certi. (TBD, ~`23.7)), Crestron Inside, Power (Smart Energy Saving, PM Mode, Wake on LAN, Network Ready), Beacon, HDMI-CEC, SI Sever Setting, webRTC, Pro:Idiom
- 

### **Environment Conditions**

- Operation Temperature: 0 °C to 40 °C (Portrait Scene : 0 °C to 35 °C)
- 
- Operation Humidity: 10 % to 80 %
- 

### **Power**

- Power Supply: AC 100-240V~, 50/60Hz
- 
- Power Type: Built-In Power
- 

### **Power Consumption**

- Typ./Max.: 105 W / 160 W
-

- Smart Energy Saving (70%): 73.5 W
- DPM: 0.5W
- Power off: 0.5W
- BTU (British Thermal Unit): 358 BTU/Hr(Typ.), 546 BTU/Hr(Max.)

**Certification**

- Safety: CB / NRTL
- EMC: FCC Class "A" / CE
- ErP: Yes

**Software Compatibility**

- SuperSign CMS: Yes
- SuperSign Control+: Yes
- SuperSign WB: Yes
- LG ConnectedCare: Yes

**Connectivity**

- Input: HDMI (3, HDCP 2.2/1.4), RS-232C In (4 Pin Phone-jack), RJ45 (LAN), USB 2.0 (2, Type A)
- Output: Audio Out, RS-232C Out (4 Pin Phone-jack)

**Sound**

- Speaker: Yes (10W x 2)

.

**Language**

- OSD: English, French, German, Spanish, Italian, Korean, Chinese(Simplified), Chinese(Original), Portugues(Brazil), Swedish, Finnish, Norwegian, Danish, Russian, Japanese, Portugues(Europe), Dutch, Czech, Greek, Türkçe, Arabic, polski

.

**Accessory**

- Basic: Remote Controller(include battery 2ea), Power Cord, Regulation Book, Phone to D-Sub9 Gender, Cable Holder

.

|                         |     |
|-------------------------|-----|
| FELÁRAS HÁZHOZSZÁLLÍTÁS | Van |
| Gyártó                  | LG  |