

# StarTech Travel HDMI or VGA USB3.0 dokkoló

illesztés: USB3.0, D-Sub kimenet: 1db, HDMI kimenet: 1db, 1Gb/s

Cikkszám: USB3SMDOCKHV

Ár:

53 460 Ft



The travel docking station for laptops lets you transform your laptop or Ultrabook™ into a mobile workstation. It adds HDMI® or VGA video output, a USB 3.0 hub port, and a Gigabit Ethernet RJ45 port, through a single USB 3.0 host connection. The travel-friendly dock helps you overcome the port limitations of modern mobile computers, making it ideal for your laptop, Microsoft Surface™ Pro 4, Surface Pro 3, Surface 3, Surface Pro 2 or Surface Book. Now, you can avoid the nuisance of carrying multiple adapters. By consolidating four essential connection ports into one convenient device, the travel dock is the the perfect laptop accessory. It features a lightweight, compact design that fits nicely into your travel bag and also features an integrated host connection cable that tucks neatly into the docking stations casing.

A versatile solution for connecting an additional display to your laptop, the travel docking station offers HDMI video output with audio, or VGA video output, providing two popular interfaces for connecting a television, projector, or monitor as a second display, with support for resolutions up to 2048x1152 (QWXGA). Leveraging the high-bandwidth (5Gbps) USB 3.0 interface to deliver flexible video output, a USB 3.0 hub port, and Gigabit Ethernet, you can quickly set up a multi-functional workstation while on the run, without sacrificing one of your laptop USB ports. Setup is seamless and hassle-free; the travel dock will automatically download the latest driver when connected to a Windows® system with an active network connection.

The USB3SMDOCKHV is backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Hardware

|                    |  |
|--------------------|--|
| 4K Support         | No   |
| Bus Type           | USB 3.0  |
| Chipset ID         | DisplayLink - DL-3700  |
| Displays Supported | 1  |
| Fast-Charge        | No   |
| Port(s)            |  |
| Industry Standards | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab                          |
|                    | USB 3.0 - Hub port supports USB 2.0/1.1 backward-compatibility |

### Performance

|                             |                                |
|-----------------------------|--------------------------------|
| Auto MDIX                   | Yes                            |
| Compatible Networks         | 10/100/1000 Mbps               |
| Full Duplex Support         | Yes                            |
| Maximum Analog Resolutions  | 2048x1152 (VGA)                |
| Maximum Data Transfer Rate  | 5 Gbps (USB 3.0)               |
|                             | 2 Gbps (Ethernet; Full-Duplex) |
| Maximum Digital Resolutions | 2048x1152 (HDMI)               |
| Type and Rate               | USB 3.0 - 5 Gbit/s             |

|                                     |   |
|-------------------------------------|---|
| UASP Support                        | Yes   |
| <b>Connector(s)</b>                 |   |
| Connector Type(s)                   | 1 - USB Type-A (9 pin) USB 3.0 Male<br><br>1 - HDMI (19 pin) Female<br>1 - VGA (15 pin; High Density D-Sub) Female<br>1 - RJ-45 Female<br>1 - USB Type-A (9 pin) USB 3.0 Female |
| <b>Software</b>                     |   |
| OS Compatibility                    | Windows® 10 (32-bit or 64-bit), 8 / 8.1 (32-bit or 64-bit), 7 (32-bit or 64-bit), Vista (32-bit or 64-bit), XP SP3 (32-bit)<br>Mac OS® 10.6 and later (tested up to 10.11)      |
| <b>Special Notes / Requirements</b> |   |
| <b>Note</b>                         | Only a single video output can be used at one time, HDMI® or VGA. If a display is connected to each video output port at the same time, then the HDMI® port will take priority  |
| System and Cable Requirements       | USB enabled computer system with available USB 3.0 port   |
| <b>Indicators</b>                   |   |
| LED Indicators                      | 1 - Link (Green)<br>1 - Activity (Yellow)   |
| <b>Power</b>                        |   |
| Power Source                        | USB-Powered   |
| <b>Environmental</b>                |   |
| Humidity                            | 90% RH  |
| Operating Temperature               | 0°C to 40°C (32°F to 104°F)   |
| Storage Temperature                 | -20°C to 70°C (-4°F to 158°F)   |
| <b>Physical Characteristics</b>     |   |
| Cable Length                        | 3.7 in [93 mm]  |
| Color                               | Black   |
| Enclosure Type                      | Plastic   |
| Product Height                      | 0.7 in [17 mm]  |
| Product Length                      | 4.9 in [125 mm]   |
| Product Weight                      | 2.8 oz [80 g]   |
| Product Width                       | 2.2 in [55 mm]  |
| <b>Packaging Information</b>        |   |
| Shipping (Package) Weight           | 6.7 oz [190 g]  |
| <b>What's in the Box</b>            |   |
| Included in Package                 | 1 - USB 3.0 Mini Docking Station<br><br>1 - Driver CD<br>1 - Instruction Manual   |

|                  |          |
|------------------|----------|
| USB-A 3.2 Gen1×1 | 1        |
| Gyártó           | StarTech |