

TP-Link Archer NX200 AX1800 Dual-Band Wi-Fi 5G/NR
router



1775Mb/s, IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), WAN (1Gb/s): 1 port, LAN (1Gb/s): 3 port, SIM kártya foglalat, 5G/NR, antennák száma: 10db, Mesh Wi-Fi, energiafelhasználás: 24W, smart home, fehér

Cikkszám: ARCHER NX200

Ár:

160 170 Ft

Garancia: 3 Év

HARDWARE FEATURES

Interface	1 × 10/100/1000 Mbps LAN/WAN Port 2 × 10/100/1000 Mbps LAN Ports 1 × Nano SIM Card Slot 2 × 5G/4G External Antenna Ports
Button	WPS Button, Reset Button, Power On/Off Button, Wi-Fi On/Off Button
External Power Supply	Power Adapter: Input Power 100-240v~50/60 Hz 0.6A Output parameter 12VDC 2A
Dimensions (W x D x H)	3.9 × 3.9 × 7.5 in (99 × 99 × 190 mm)
Antenna	8 × 5G/LTE Internal Antennas 2 × Wi-Fi Internal Antennas

WIRELESS FEATURES

Wireless Standards	IEEE 802.11ax/ac/n/a 5 GHz IEEE 802.11ax/n/b/g 2.4 GHz
Frequency	2.4 GHz and 5 GHz
Signal Rate	574 Mbps at 2.4 GHz, 1201 Mbps at 5 GHz 5GHz: 11a 54M:-80 dBm 11ax HE20:-68 dBm 11ax HE40:-65 dBm 11ax HE80:-62 dBm 11ac VHT20:-76 dBm 11ac VHT40:-72 dBm 11ac VHT80:-68 dBm
Reception Sensitivity	11n HT20:-79 dBm 11n HT40:-75 dBm 2.4GHz 11g 54M:-78 dBm 11ax HE20:-65 dBm 11ax HE40:-62 dBm 11ac VHT20:-73 dBm 11ac VHT40:-68 dBm 11n HT20:-75 dBm 11n HT40:-72 dBm
Transmit Power	<23dBm (5.15GHz~5.35GHz) <30dBm (5.47GHz~5.71GHz) <20dBm (2.4GHz)
Wireless	Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless

Functions	Statistics
WAN Failover	Yes
Wireless Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
	5G: N1/N3/N5/N7/N8/N20/N28/N38/N40/N41/N77/N78 (2100/1800/850/2600/900/800/700/2600/2300/2500/3700/3500 MHz)
Network Type	FDD-LTE: B1/B3/B5/B7/B8/B20/B28/B32 (2100/1800/850/2600/900/800/700/1500 MHz)
	TDD-LTE: B38/B40/B41/B42/B43 (2600/2300/2500/3500/3700 MHz)
	DC-HSDPA/HSPA+/HSPA/UMTS: B1/B5/B8 (2100/850/900 MHz)

SOFTWARE FEATURES

Quality of Service	Prioritizes network traffic by device or application
Security	DoS, IPv4 SPI Firewall, IPv6 Firewal, IP and MAC Address Binding, Access Control
WAN Type	Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
Management	TP-Link Cloud, Local Management, Remote Management
DHCP	Server, DHCP Client List, Address Reservation
Port Forwarding	ALG, Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	TP-Link, DynDns, NO-IP
VPN	PPTP VPN, IPSec VPN , OpenVPN
Access Control	Parental Control, Local Management Control
Firewall Security	DoS, SPI Firewall, IP Address Filter/Domain Filter, IP and MAC Address Binding
Protocols	IPv4, IPv6
Guest Network	2.4 GHz Guest Network x 1
	5 GHz Guest Network x 1

OTHERS

Certification	CE, RoHS
	5G AX1800 Wireless Dual-Band Gigabit Router Archer NX200
Package Contents	1.5m Power Adapter
	RJ45 Ethernet Cable
	Quick Installation Guide
	Microsoft Windows 98SE/NT/2000/XP/Vista™/7/8/8.1/10, MAC OS, NetWare, UNIX or Linux
System Requirements	Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser
	Nano SIM Card
	Operating Temperature: 0?~40? (32? ~104?)
Environment	Storage Temperature: -40?~70? (-40? ~158?)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

Dual-Band	Van
Dual-personality Ethernet port	1
energiafelhasználás	24
LAN (1Gb/s)	3
Mesh Wi-Fi	Van
SIM kártya foglalat	Van
smart home	Van
WAN (1Gb/s)	1
Wi-Fi átviteli sebesség	1775
Wi-Fi jel típus	IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6)
Wi-Fi titkosítás	WPA2-PSK

Gyártó	TP-Link
antenna típusa	belső
antennák száma	10
mobil internet	5G/NR
szülői felügyelet	Van
WI-FI	Van
szín	fehér