

StarTech USB-A 3.0 -> VGA M/F adapter 0.06m fekete

Cikkszám: USB32VGAES

Ár:

18 380 Ft



The USB32VGAES Slim USB 3.0 to VGA Adapter turns a USB 3.0 port into a VGA output port with 1920x1200/1080p video support. The adapter minimizes clutter with a slim design that seamlessly blends with your video cable - an ideal space-saving solution for multi-monitor applications on Ultrabook™, laptop, or desktop computers.

Functioning as an external graphics card, this USB to VGA adapter provides a convenient way to add multi-monitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0).

To save space while travelling, this ultra-portable USB to VGA adapter features a lightweight, small footprint design that fits easily in a laptop carrying bag.

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter delivers smooth, high-definition content to your VGA display/projector. The adapter can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

The USB32VGAES is backed by a StarTech.com 2-year warranty and free lifetime technical support.

ERROR

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

USB 3.0 port (Backwards compatible with USB 2.0)

Hardware

Chipset ID	T5-302/MCT
Ports	1
USB Pass-Through	No

Performance

General Specifications This USB video adapter uses a Trigger family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a DisplayLink or Fresco family chipset.

Maximum Analog Resolutions 1920x1200/1080p

Supported Resolutions Widescreen(16/32 bit): 1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720

Standard(16/32 bit):

	1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600
Wide Screen	Yes
Supported	
Connector(s)	
Connector A	1 - USB Type-A (9 pin) USB 3.0 Male Input
Connector B	1 - VGA (15 pin; High Density D-Sub) Female Output
Software	
Microsoft	Yes
WHQL	
Certified	
OS	Windows® 10 (32/64)
Compatibility	Windows 8 / 8.1 (32/64)
	Windows 7(32/64)
	Windows Vista (32/64)
	Windows XP (32/64)
Special Notes / Requirements	
Note	Connect a maximum of five USB32VGAES adapters on a single PC - See manual for system requirements
System and	CPU: i3 Dual core 2.8GHz
Cable	RAM: 2GB or higher
Requirements	Full HD Video:
	CPU: Quad Core 2.4GHz or Higher (i5 recommended)
	RAM: 4GB or higher
Power	
Power Source	USB-Powered
Environmental	
Humidity	< 85% non-condensing
Operating	0°C to 50°C (32°F to 122°F)
Temperature	
Storage	-10°C to 75°C (14°F to 167°F)
Temperature	
Physical Characteristics	
Cable Length	2.4 in [62 mm]
Color	Black
Enclosure	Plastic
Type	
Product	0.5 in [12 mm]
Height	
Product	7.5 in [190 mm]
Length	
Product	0.9 oz [25 g]
Weight	
Product Width	1 in [25 mm]
Packaging Information	
Shipping	0 lb [0 kg]
(Package)	
Weight	
What's in the Box	
Included in	1 - Slim USB 3.0 Video Adapter
Package	
	1 - Driver CD
	1 - Instruction Manual

