

TP-Link VIGI C385 Bullet smart home kültéri IP kamera IP67



8MP, 2,8mm F1.6 1/2,7" CMOS, Ethernet (100Mb/s), PoE, beépített mikrofon, beépített hangszóró, forgatható, 3840x2160, 25fps, alakfelismerés, mozgásérzékelő, éjszakai mód, microSD, fehér, H.265+;H.264+, 525g

Cikkszám: VIGI C385 (2.8MM)

Ár:

138 110 Ft

Garancia: 3 Év

KAMERA

Képérzékelő

1/2.7" Progressive Scan CMOS

Day/Night Switch

Unified/ Scheduled/ Auto

Shutter Speed

1/3 to 1/10000 s

Slow Shutter

Yes

Min. szükséges megvilágítás 0.005 Lux; 0 Lux with IR/White light

Day/Night Mechanism

IR Cut Filter

LENS

Type

Fixed Focal Lens

Focal Length

2.8/4 mm

Aperture

F1.6

• 2.8 mm:

Horizontal FOV: 111.4°, Vertical FOV: 58.8°, Diagonal FOV: 134°

FOV

• 4 mm:

Horizontal FOV: 91.5°, Vertical FOV: 46.1°, Diagonal FOV: 109.6°

Lens Mount

M12*P 0.5

• 2.8 mm

Detect: 85 m (278 ft)

Observe: 35 m (116 ft)

Recognize: 17 m (56 ft)

Identify: 8 m (28 ft)

DORI Distance

• 4 mm

Detect: 107 m (350 ft)

Observe: 44 m (146 ft)

Recognize: 21 m (70 ft)

Identify: 11 m (35 ft)

ANGLE ADJUSTMENT (MANUAL)

Range Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°

ILLUMINATOR

IR LED

• Quantity: 2

• Range: 30m

• Wavelength: 850nm

White LED

• Quantity: 2

• Range: 30m

Illuminator On/Off Control Auto/Scheduled/Always on/Always off

VIDEO

Max. Resolution	3840 X 2160 Frame Rate: 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
Main Stream	- Resolution: 3840x2160, 2560x1440, 2304x1296, 2048x1280, 1920x1080, 1280x720 Note: - If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps. - If 120dB is turned on, the frame rate can only support up to 20fps. Frame Rate: 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
Sub-Stream	Resolution: 704x576,640x480, 352x288, 320x240 Note: - If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps. - If 120dB is turned on, the frame rate can only support up to 20fps.
Bit Rate Control	CBR, VBR
Video Compression	- Main Stream: H.265+/H.265/H.264+/H.264 - Sub-Stream: H.265/H.264
H.264 Type	High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile*
H.265+	Main Stream Supported*
Video Bit Rate	- Main Stream: 256 Kbps to 6 Mbps - Sub-Stream: 64 Kbps to 512 Kbps
IMAGE	
Image Settings	- Mirror - Brightness - Contrast - Saturation - Sharpness - Exposure - WDR - White Balance - Prevent Overexposure to Infrared Light - HLC Adjustable by Client Software
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	120 dB
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
HANG	
Hangkommunikáció	Two-Way Audio
Hangbemenet	Yes
Hangkimenet	Yes
Hangtömrítés	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps(G.711 alaw)
HÁLÓZAT	
Szabvány	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
ONVIF	Yes
API	Open Network Video Interface (Profile S)

Simultaneous Live View	3 Main Streams & 3 Sub-Streams
Client	VIGI App, VIGI Security Manager, Web UI, VIGI VMS • Google Chrome® 57 and above
Web Browser	• Firefox® 52 and above • Safari® 11 and above • Microsoft® Edge 91 and above
Cloud	Yes
Biztonság	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
FIGYELMEZTETÉSI ÉS ESEMÉNYKEZELÉSI VEZÉRLÉS	
Smart Event	• Human & Vehicle Classification • Intrusion Detection • Line-Crossing Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned Detection • Object Removal Detection • Loitering Detection • Smart Frame • People Detection • Vehicle Detection • Motion Detection
	• Video Tampering Detection
	• Exception (Illegal Login)
	• Scene Change Detection
	• Memory Card Video Recording
	• Message Push
	• Audible Warning
	• White Light Flashing
Basic Event	
Alarm Linkage	
Linkage Method	N/A
Output Notification	Message Push
FIZIKAI KEZELŐFELÜLET	
Hálózati csatlakozás	1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE
Alarm	N/A
Reset Button	Yes
Power	DC Power Port
On-board Storage	Built-In Memory Card Slot, Support MicroSD Card, up to 256 GB**
Built-in Microphone	Yes; Records Anything Going on within a 15-ft Radius of the Camera
Built-in Speaker	Yes
Audio	N/A
ÁLTALÁNOS	
Operating Temperature	-30-60 °C
Storage Temperature	-40-60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing)
Csomagolás tartalma	• VIGI Network Camera
	• Quick Start Guide
	• Waterproof Cable Attachments
	• Mounting Accessories
Material	Metal
Net Weight	0.525 Kg
Power Supply	• 12V DC ± 5%, Max. 10.5 W, 5.5 mm Coaxial Power Plug
	• PoE: 802.3af/at, class 0, Max. 11.5 W
Protection	IP67
Product Dimensions (L x W x H)	74 × 184 × 74 mm
Certifications	CE, NTRA, VCCI, KC, BSMI, FCC, IC

alakfelismerés	Van
beépített hangszóró	mono
érzékelő felbontása	8MP

látószög	134°
smart home	Van
tömeg	525
videó felbontása	3840x2160
Gyártó	TP-Link
beépített mikrofon	Van
cikknév kiegészítés	IP67
csatlakozó	Ethernet (100Mb/s)
döntési szög	90
éjszakai mód	Van
érzékelő típusa	2,8mm F1.6 1/2,7" CMOS
forgatási szög	360
forgatható	Van
kamera rögzítés típusa	falra rögzíthető
memóriakártya foglalat	microSD
mozgásérzékelő	Van
PoE	Van
rögzítési formátumok	H.265+;H.264+
rögzítési sebesség	25
szín	fehér