

TP-Link TL-FC111A-20 WDM 100Mb/s Ethernet média
konverter (20km)

RJ45: 1db, szürke
Cikkszám: TL-FC111A-20
Ár:
10 800 Ft



Garancia: 5 Év

NETWORK

Standards and ProtocolsIEEE802.3, IEEE802.3i, IEEE802.3u

ENVIRONMENT

Operating Temperature0°C to 50°C (32°F to 122°F)

Storage Temperature-40°C to 70°C (-40°F to 158°F)

Operating Humidity10% to 90% RH non-condensing

Storage Humidity5% to 90% RH non-condensing

HARDWARE FEATURES

Network Media100BASE-Tx: 2-pair UTP/STP of Cat. 5 or above (≤100 m)

Power SupplyExternal Power Adapter: 5 V/0.6 A

LED PWR, Link/Act

Dimensions (W x D x H)94.5*73*27 mm

Wave Length1550 nm TX, 1310 nm RX

ANTENNA

Connector Type1 SC fiber optic, 1 RJ45 jack

MEDIA CONVERTER & MODULE

Standards and Protocols IEEE 802.3, IEEE 802.3i, IEEE802.3u
Auto-negotiation of half-duplex / full-duplex transfer mode

Basic Function Full-duplex flow control (IEEE 802.3x)
Half-duplex flow control (Backpressure)
Extends fiber distance up to 20km (12.4 miles)

Ports 1x 100M single SC/UPC port
1x 10/100M RJ45 port (Auto MDI/MDIX)

WDM TX 1550 nm

WDM RX 1310 nm

Network Media 10BASE-T UTP category 3, 4, 5 cable (maximum 100m)
EIA/TIA-568 100Ω STP (maximum 100m)

Network Media 100BASE-T UTP category 5, 5e cable (maximum 100m)
EIA/TIA-568 100Ω STP (maximum 100m)

Network Media 100BASE-FXSingle-mode fiber

LED Indicators PWR, Link/Act

Dimensions (W*D*H) 3.7 × 2.9 × 1.1 in.
(95 × 73 × 27 mm)

Power Supply External Power Adapter: 5 V/0.6 A

Safety & Emission FCC, CE, RoHS

Fiber Type 9/125 μm single-mode fber (≤20 km)
Operating Temperature: 0?~50? (32?~122?)
Storage Temperature: -40?~70? (-40?~158?)

Environment

Storage Temperature: -40:~70: (-40:~100:)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing

Gyártó

TP-Link