

TP-Link DS110GMP Omada PoE switch

LAN (1Gb/s): 10 port, SFP: 1db, energiafelhasználás: 141,4W, szürke
Cikkszám: DS110GMP

Ár:
88 900 Ft



Garancia: 5 Év

HARDWARE FEATURES

Interface

- 9× 10/100/1000 Mbps RJ45 Ports
- 1× 1000 Mbps Combo SFP/RJ45 Port
- AUTO Negotiation
- AUTO MDI/MDIX

Network Media

- 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
- EIA/TIA-568 100? STP (maximum 100m)
- 100BASE-TX: UTP category 5, 5e cable (maximum 100m)
- EIA/TIA-568 100? STP (maximum 100m)
- 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m)
- EIA/TIA-568 100? STP (maximum 100m)

Fan Quantity

Fanless

Physical Security Lock

Yes

External Power Supply

External Power Adapter (Output: 53.5VDC / 2.43A)

Packet Forwarding Rate

14.88 Mpps

PoE Ports (RJ45)

- Standard: 802.3 af/at compliant
- PoE Ports: Ports 1-8
- Power Supply: 123 W

Mac Address Table

4K

Jumbo Frame

16 KB

Switching Capacity

20 Gbps

Dimensions (W x D x H)

- 8.2 × 4.9 × 1.0 in (209 × 126 × 26 mm)
- 7.93 W (220V / 50Hz with no PD connected)
 - 141.40 W (220V / 50Hz with 123 W PD connected)
 - 27.04 BTU/h (220V / 50Hz with no PD connected)
 - 482.17 BTU/h (220V / 50Hz with 123 W PD connected)

Max Power Consumption

Max Heat Dissipation

SOFTWARE FEATURES

Transmission Method

- Store-And-Forward
- Compatible With IEEE 802.3af/at Compliant PDs
 - Extend Mode: Ports 1-4
 - Priority Mode: Ports 1-2

Advanced Functions

- Isolation Mode: Ports 1-4/5-8
- PoE Auto Recovery: Ports 1-8
- Mac Address Auto-Learning and Auto-Aging
- IEEE802.3x Flow Control for Full-Duplex Mode and Backpressure for Half-Duplex Mode

OTHERS

Certification

- FCC, CE, RoHS
- DS110GMP

Package Contents

- Power Adapter

Environment

- Installation Guide
- Operating Temperature: 0–40 ° (32–104 °)
- Storage Temperature: -40–70 ° (-40–158 °)
- Operating Humidity: 10–90% RH non-condensing
- Storage Humidity: 5–90% RH non-condensing

Dual-personality Ethernet port	1
energiafelhasználás	141.4
LAN (1Gb/s)	10
PoE port	8
SFP	1
Gyártó	TP-Link
PoE	Van
szín	szürke