

StarTech PCI-E x1 1+2 portos FireWire A FireWire B IO vezérlő

illesztés: PCIe x1, FireWire A, FireWire B, low profile, PCI-E x1: 1db

Cikkszám: PEX1394B3

Ár:

47 170 Ft



This 3 Port PCI Express FireWire adapter card can be installed in a PCI Express slot to add two IEEE1394b (FireWire 800 - 9 pin) ports and one IEEE1394a (FireWire 400 - 6 pin) port, providing broad compatibility with a wide range of FireWire devices (e.g. DV camcorders, external hard drives, digital cameras, etc.).

The 2b, 1a card features a native (single chip) PCI Express chipset - resulting in faster, more reliable and cost effective performance than expansion cards that utilize a "bridge" chip.

The StarTech.com Advantage

- Add 3 FireWire ports to a standard or small form factor (SFF) computer with support for high-powered FireWire devices
- Utilizes a native PCI Express chipset design rather than a bridge chip, ensuring a fast, reliable and cost-effective FireWire expansion
- Backed by a StarTech.com lifetime warranty and free lifetime technical support

Bus Type	PCI Express
Card Type	Standard Profile (LP bracket incl.)
Chipset ID	LSI/Agere - FW643
Industry Standards	IEEE-1394/1394A/1394B

OHCI
PCI 2.2

Interface	FireWire 800 (1394b)
Ports	3

Performance

Maximum Data Transfer Rate	800 Mbps
----------------------------	----------

Connector(s)

Connector Type(s)	1 - PCI Express x1 Male
External Ports	1 - Firewire 400 (6 pin; IEEE 1394a) Female 2 - Firewire 800 (9 pin; IEEE 1394b) Female
Internal Ports	1 - SP4 (4 pin; Small Drive Power) Male

Software

OS Compatibility	Windows® 10 (32/64), 8 / 8.1 (32/64), 7 (32/64), Vista (32/64), XP (32/64), 2000, ME, 98SE Windows Server® 2012, 2008 R2, 2003 Mac OS® 10.x (tested up to 10.11) Linux
------------------	---

Special Notes / Requirements

Note	The software included with this product supports a "typical" driver install only. Custom driver setup requires software purchase from a 3rd party
System and Cable	PCI Express enabled computer with an available PCI Express x1 slot or higher

Requirements

Environmental

Humidity 0~90% RH
Operating 0°C to 70°C (32°F to 158°C)
Temperature
Storage Temperature-20°C to 90°C (-4°F to 194°C)

Physical Characteristics

Product Height 4.7 in [120 mm]
Product Length 3.5 in [90 mm]
Product Weight 1.8 oz [50 g]
Product Width 0.7 in [18 mm]

Packaging Information

Shipping (Package) 0.5 lb [0.2 kg]
Weight

What's in the Box

- Included in Package
- 1 - PCI Express FireWire Card
 - 1 - FireWire cable
 - 1 - Low Profile Bracket
 - 1 - Software CD
 - 1 - Instruction Manual