

TP-Link VIGI NVR1004H-4P 2TB hálózati video rögzítő NVR



beépíthető meghajtók száma: 1db, SATA3, USB2.0, D-Sub: 1db, HDMI
kimenet: 1db, LAN (100Mb/s): 5db, 4-csatornás, PoE: 4db, H.265+, fekete
Cikkszám: VIGI NVR1004H-4P-2TB

Ár:
327 590 Ft

Video and Audio	
IP Video Input	4-Channel
Incoming Bandwidth	80 Mbps
Outgoing Bandwidth	60 Mbps
HDMI Output	1 Channel, Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1680x1050/60Hz,
Resolution	1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
VGA Output	1 Channel, Resolution: 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz,
Resolution	1280x1024/60Hz, 1280x720/60Hz
Video Output Mode	HDMI/VGA Simultaneous Output
Multi-View Display	04.jan
DECODING	
Audio Compression	G.711A/G.711U/G.726
Decoding Format	H.265+/H.265/ H.264+/H.264
Video Compression	H.265+/H.265/ H.264+/H.264
Record Resolution	8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Live View/Playback	8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/
Resolution	DCIF/2CIF/CIF/QCIF
Synchronous	
Playback	4 Channel
Capability	2-ch @ 8MP, 4-ch @ 4MP
Record Management	
Record Mode	• Manual Recording • Scheduling Recording • Motion Detection Recording • Instant Playback
Playback Mode	• Regular Playback • Tag Playback • Event Playback
Backup Mode	• Regular Backup • Video Clip Backup • Play • Pause • Stop • Fast Forward • Fast Backward
Playback Function	• Play By Frame • Full Screen • Video Clip • Export Clip • Digital Zoom

	• Lock Recording • Audio On/Off
Hálózat	
Szabvány	TCP/IP, DHCP, DNS, NTP, UPnP
Mobile Phone Access	Android, iOS
Incoming Bandwidth	80 Mbps
Outgoing Bandwidth	60 Mbps
Web Browser Interoperability	Chrome (57+), Firefox (52+), Edge (91+)
External Interface	ONVIF, CGI
Network Interface	1, RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface
USB Interface	1 Front USB 2.0 Port, 1 Rear USB 2.0 Port
Audio Interface	1, Audio In; 1, Audio Out
Alarm In/Out	N/A
Serial Interface	N/A
Power	1× DC Jack
Reset Button	1
Speaker	N/A
eSATA	N/A
HDMI	1
VGA	1
HARD DISK	
SATA	1 SATA Interface
Capacity	Up to 10 TB
PoE	
Standard	802.3at/af Compliant
Interface	1- 4, RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface
PoE Budget	53 W ² Available for All PoE+ Ports, 30 W Max per Port
Alarm	
	• Motion Detection • Video Tampering • Line-Crossing Detection • Intrusion Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned/Removal Detection • Vehicle Detection • Human Detection • Smart Frame • Video Loss
General Alarm	
	• Offline and IP Conflict • Disk Exception • Login Exception • Recording • White Light Alarm
Anomaly Alarm	
	• Buzzer • Log • Audible Alarm
Alarm Linkage	
Fizikai kezelőfelület	
Hálózati csatlakozás	1 RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface
USB Interface	2× USB 2.0
Általános	
Operating Temperature	-10-55 °C
Storage Temperature	-40-70 °C
Storage Humidity	10%~90% RH Non-Condensing
	VIGI Network Video Recorder
	Power Adapter
Csomagolás tartalma	HDD Screws
	Mouse

Working Temperature	Quick Installation Guide
Working Humidity	• NVR: -10-55 °C
Méreték (Sz x Mé x Ma)	• Power Adapter: 0-40 °C
PoE	10%~90% RH Non-Condensing
Külső tápellátás	246.2 × 148.2 × 45 mm
Power Supply	Standard: 802.3af/at
Power Consumption	PoE Ports: Ports 1-4
Certifications	PoE Budget: 53 W
Videó/Kép	53.5V DC/1.31A
Video Input	53.5V DC/1.31A
Recording	4.25 W (without disk)
Resolution	CE, EAC, UKCA, RCM, Triman, BSMI, VCCI, FCC, IC, HDMI
HDMI Output	4-Channel IP Video Input, up to 8MP Resolution
Resolution	8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
VGA Output	1 Channel, Resolution: 3840x2160/30Hz,1920x1080/60Hz,1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1024x768/60Hz, 1280x720/60Hz
Resolution	1 Channel, Resolution: 1920x1080/60Hz,1680x1050/60Hz,1440x900/60Hz, 1280x1024/60Hz, 1024x768/60Hz, 1280x720/60Hz

cikk kiegészítés	4-csatornás, PoE: 4db, H.265+
kapacitás	2TB
LAN (100Mb/s)	5
Gyártó	TP-Link
audió kimenet	1
beépíthető meghajtók száma	1
belső csatlakozó	SATA3
D-Sub	1
fogyasztás	60
USB2.0	2 db
szín	fekete