

TP-Link SG3218XP-M2 Omada PoE rack switch

LAN (2,5Gb/s): 16 port, USB2.0, SFP+: 2db, menedzselhető,
energiafelhasználás: 299,4W, szürke

Cikkszám: SG3218XP-M2

Ár:

328 030 Ft



HARDVER JELLEMZŐK

Csatlakozások

- 16× 2.5 Gbps RJ45 Ports
- 2× 10G SFP+ Slots
- 1× RJ45 Console Port
- 1× Micro-USB Console Port

Ventilátorok száma

2

Hálózati tápegység

100-240 V AC~50/60 Hz

- Standard: 802.3at/af compliant

PoE portok (RJ45)

- PoE+ Ports(802.3at PoE): 8 Ports, up to 30 W per port
- Power Budget: 240 W

Méretek (Sz x Mé x Ma)

17.3 × 7.1 × 1.7 in (440 × 180 × 44 mm)

Felszerelés

Rack Mountable

Max. áramfelvétel

299.4 W (110V/60Hz)(with 240 W PD connected)

Max Heat Dissipation

1021.64 BTU/h (110 V/60 Hz)(with 240 W PD connected)

MŰKÖDÉSI JELLEMZŐK

Switching teljesítmény

120 Gbps

Csomagtovábbítási sebesség

89.28 Mpps

Fizikai (MAC) cím tábla

16 K

Csomag puffer memória

12 Mbit

Jumbo Frame

9 KB

SZOFTVER JELLEMZŐK

QoS (szolgáltatás minősége)

- 8 priority queues
- 802.1p CoS/DSCP priority
- Queue scheduling
 - SP (Strict Priority)
 - WRR (Weighted Round Robin)
 - SP+WRR
- Bandwidth Control
 - Port/Flow based Rating Limiting
- Smoother Performance
- Action for Flows
 - Mirror (to supported interface)
 - Redirect (to supported interface)
 - Rate Limit
 - QoS Remark
- 32 IPv4/IPv6 Interfaces
- Static Routing
 - 48 static routes
- Static ARP
 - 128 Static Entries

L3 jellemzők

- Proxy ARP
- Gratuitous ARP
- DHCP Server
- DHCP Relay
 - DHCP Interface Relay
 - DHCP VLAN Relay
- DHCP L2 Relay
- Link Aggregation
 - static link aggregation
 - 802.3ad LACP
 - Up to 8 aggregation groups, containing 8 ports per group
- Spanning Tree Protocol
 - 802.1d STP
 - 802.1w RSTP
 - 802.1s MSTP
 - STP Security: TC Protect, BPDU Filter, Root Protect
- Loopback Detection

L2 és L2+ jellemzők

- Port based
- VLAN based
- Flow Control
 - 802.3x Flow Control
- HOL Blocking Prevention
- Mirroring
 - Port Mirroring
 - CPU Mirroring
 - One-to-One
 - Many-to-One
 - Tx/Rx/Both
- IGMP Snooping
 - IGMP v1/v2/v3 Snooping
 - Fast Leave
 - IGMP Snooping Querier
 - IGMP Authentication
- IGMP Authentication

L2 Multicast

- MLD Snooping
 - MLD v1/v2 Snooping
 - Fast Leave
 - MLD Snooping Querier
 - Static Group Config
 - Limited IP Multicast
- MVR
 - Multicast Filtering: 256 profiles and 16 entries per profile
 - Automatic Device Discovery
 - Batch Configuration
 - Batch Firmware Upgrading

További jellemzők

- Intelligent Network Monitoring
- Abnormal Event Warnings
- Unified Configuration
- Reboot Schedule
- VLAN Group
 - Max 4K VLAN Groups
- 802.1Q Tagged VLAN
- MAC VLAN: 256 Entries
- Protocol VLAN: Protocol Template 16, Protocol VLAN 16
- GVRP
- VLAN VPN (QinQ)
 - Port-Based QinQ
 - Selective QinQ
- Voice VLAN
- Time-based ACL
- MAC ACL
- Source MAC

VLAN

- Destination MAC
- VLAN ID
- User Priority
- Ether Type
- IP ACL
- Source IP
- Destination IP
- Fragment
- IP Protocol

Hozzáférés-jogosultsági lista (ACL)

- TCP Flag
- TCP/UDP Port
- DSCP/IP TOS
- User Priority
- Combined ACL
- Packet Content ACL
- IPv6 ACL
- Policy
- Mirroring
- Redirect
- Rate Limit
- QoS Remark
- ACL apply to Port/VLAN
- IP-MAC-Port Binding
- 512 Entries
- DHCP Snooping
- ARP Inspection
- IPv4 Source Guard: 100 Entries
- IPv6-MAC-Port Binding
- 512 Entries
- DHCPv6 Snooping
- ND Detection
- IPv6 Source Guard: 100 Entries
- DoS Defend
- Static/Dynamic Port Security
- Up to 64 MAC addresses per port

Biztonság

- Broadcast/Multicast/Unicast Storm Control
- kbps/ratio control mode
- 802.1X
- Port base authentication
- Mac base authentication
- VLAN Assignment
- MAB
- Guest VLAN
- Support Radius authentication and accountability
- AAA (including TACACS+)
- Port Isolation
- Secure web management through HTTPS with SSLv3/TLS 1.2
- Secure Command Line Interface (CLI) management with SSHv1/SSHv2
- IP/Port/MAC based access control
- IPv6 Dual IPv4/IPv6
- Multicast Listener Discovery (MLD) Snooping
- IPv6 ACL
- IPv6 Interface
- Static IPv6 Routing
- IPv6 neighbor discovery (ND)
- Path maximum transmission unit (MTU) discovery
- Internet Control Message Protocol (ICMP) version 6
- TCPv6/UDPv6
- IPv6 applications
- DHCPv6 Client
- Ping6

IPv6

- Tracert6
- Telnet (v6)
- IPv6 SNMP
- IPv6 SSH
- IPv6 SSL
- Http/Https
- IPv6 TFTP
- MIB II (RFC1213)
- Interface MIB (RFC2233)
- Ethernet Interface MIB (RFC1643)
- Bridge MIB (RFC1493)
- P/Q-Bridge MIB (RFC2674)
- RMON MIB (RFC2819)
- RMON2 MIB (RFC2021)
- Radius Accounting Client MIB (RFC2620)
- Radius Authentication Client MIB (RFC2618)
- Remote Ping, Traceroute MIB (RFC2925)
- Support TP-Link private MIB

MIBs

VEZÉRLÉS

Omada App

Yes. Requiring the use of OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller.

Centralized Management

- Omada Cloud-Based Controller
- Omada Hardware Controller (OC300)
- Omada Hardware Controller (OC200)
- Omada Software Controller

Cloud Access

Yes. Requiring the use of OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller.

Zero-Touch Provisioning

Yes. Requiring the use of Omada Cloud-Based Controller.

Management Features

- Web-based GUI
- Command Line Interface (CLI) through the console port, telnet
- SNMP v1/v2c/v3
- Trap/Inform
- RMON (1,2,3,9 groups)
- SDM Template
- DHCP/BOOTP Client
- 802.1ab LLDP/LLDP-MED
- DHCP AutoInstall
- Dual Image, Dual Configuration
- CPU Monitoring
- Cable Diagnostics
- EEE
- Password Recovery
- SNTP
- System Log

EGYÉB JELLEMZŐK

Tanúsítványok

- CE, FCC, RoHS
- SG3218XP-M2 Switch
 - Power Cord

Csomagolás tartalma

- Quick Installation Guide
- Rackmount Kit
- Rubber Feet

Rendszerkövetelmény

Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7/8/10/11, MAC® OS, NetWare®, UNIX® or Linux.

Környezet

- Operating Temperature: 0-50 ° (32-122 °);
- Storage Temperature: -40-70 ° (-40-158 °)
- Operating Humidity: 10-90% RH non-condensing
- Storage Humidity: 5-90% RH non-condensing

