

Dahua CS4010-8ET-60 PoE switch

LAN (100Mb/s): 8 port, LAN (1Gb/s): 2 port, menedzselhető,
energiafelhasználás: 65W, fekete

Cikkszám: CS4010-8ET-60

Ár:

33 320 Ft



Garancia: 36 Hónap	
Layer	Layer 2
Switching Capacity	4.8 Gbps
Packet Forwarding Rate	3.57 Mpps
Description of Function Slots	Port 1-8: 4 × RJ-45 10/100 Mbps (PoE); Port 9-10: 2 × RJ-45 10/100/1000 Mbps (uplink)
PoE Power	Port 1 ? 60 W, Port 2-8 ? 30 W, total ? 60 W
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	5% -95% (RH), non-condensing
Power Consumption	Idling: ?3 W; Full load: 65 W
Power Supply	External power supply: 53 VDC, 1.226 A
Statics Protection	Air discharge: 8 kV; Contact discharge: 6 kV
Lightning Protection	Common mode: 4 kV; Differential mode: 2 kV
Net Weight	0.28 kg (0.64 lb)
Product Dimensions	130 mm × 90 mm × 26 mm (5.11" × 3.54" × 1.02") (L × W × H)
Gross Weight	0.80 kg (1.76 lb)
Packaging Dimensions	265 mm × 238 mm × 76 mm (10.43" × 9.37" × 2.99") (L × W × H)
Casing Material	Sheet metal
Installation	Desktop mount; wall mount
Certifications	CE
Packing List	Quick Start Guide × 1; Legal and Regulatory Information × 1;Power adapter × 1; Power cord × 1
Modular Switch/Fixed Switch	Fixed
Included Power Adapter	Yes
PoE	Yes
Ethernet Port	4
Reset Button	1
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Humidity	5%-95% (RH), non-condensing
Recommended Video Channels	4-ch 4-MP IPC
MTBF	232.62 years
Packet Buffer Size	4 Mbit
Jumbo Frame	9216 Byte
MAC Table Size	8K
VLAN Number	32
Communication Standard	IEEE802.3; IEEE802.3u; IEEE802.3x; IEEE802.3ab
PoE Protocol	IEEE802.3af; IEEE802.3at; Hi-PoE
PoE Power Consumption Management	Yes
PoE Pin Assignment	1,2,4,5(V+),3,6,7,8(V-)

Long Distance PoE Transmission	Yes
VLAN Function	Port-based VLAN
IEEE 802.3x Flow Control	Yes
DHCP Function	DHCP Client
Equipment Management	Web management; App management
BasicGeneralHardwarePerformanceFeature	

Gyártó

Dahua