

LG 43UH5N-E Digital Signage 24/7 43" IPS LED smart LFD
monitor fekete



43", 3840x2160, 16:9, 500cd/m2, 1000:1, 8ms, USB2.0, HDMI, DisplayPort, LAN, Wi-Fi, PIP/PBP, hangszóró, falra szerelhető (VESA), portré mód (pivot), dönthető (tilt), 120W

Cikkszám: 43UH5N-E

Ár:

371 260 Ft

43UH5N-E
UHD Signage Display



Tech Spec

Panel

- Screen Size: 43"

- Panel Technology: IPS

- Back Light Type: Edge

- Aspect Ratio: 16:9

-
- Native Resolution: 3,840 X 2,160 (UHD)
-
- Refresh Rate: 60 Hz
-
- Brightness (Typ.): 500 nit
-
- Contrast Ratio: 1,000 : 1
-
- Dynamic CR: 1,000,000 : 1
-
- Color gamut: BT709 95%
-
- Viewing Angle (H x V): 178 × 178
-
- Color Depth: 10bit(D), 1.07Billion colors
-
- Response Time: Tr : 8ms / Tf :10ms
-
- Surface Treatment (Haze): 28%
-
- Life Time (Min.): 50,000 Hrs
-
- Operation Hours (Hours / Days): 24 / 7
-
- Portrait / Landscape: Yes / Yes
-

Mechanical Specification

-
- Bezel Color: Black
-
- Bezel Width: 8.9 mm (T/R/L), 12.9 mm (B)
-
- Weight (Head): 11.1 kg
-
- Packed Weight: 12.8 kg
-

- Monitor Dimensions (W × H × D): 963 x 556.2 x 29.7mm (without IR)

- Carton Dimensions (W × H × D): 1,055 x 660 x 142 mm

- Handle: No

- VESA™ Standard Mount Interface: 200 × 200 mm

Key Feature

- Internal Memory 16 GB, Built-in Wi-Fi, Sensor (Temperature Sensor, Auto Brightness Sensor (External IR), Acceleration (Gyro) Sensor), Local Key Operation, Built-in Speaker, webOS 6.0, Local Contents Scheduling, Group Manager, USB Plug & Play, Fail Over, Image (Booting Logo Image, No Signal Image), Sync (RS-232C Sync, Local Network Sync), PIP, PBP (4), Screen Share, Video Tag (4), Play via URL, Rotation (Screen Rotation, External Input Rotation), Gapless Playback, Tile Mode Setting (Max. 15 × 15), Setting Data Cloning, SNMP, ISM Method, Auto Set ID, Status Mailing, Control Manager, 3rd Party Compatibility (Cisco Certi, Crestron Connected®), Smart Energy Saving, PM Mode, Wake on LAN, Network Ready, Beacon, HDMI-CEC, SI Server Setting, webRTC, Pro:Idiom

Environment Conditions

- Operation Temperature: 0 °C to 40 °C
- Operation Humidity: 10 % to 80 %

Power

- Power Supply: AC 100-240 V ~, 50/60 Hz
- Power Type: Built-In Power

Power Consumption

- Typ./Max.: 80W / 120W
- Smart Energy Saving (70%): 56W

- DPM: 0.5W
- Power off: 0.5W
- BTU (British Thermal Unit): 273 BTU/Hr(Typ.), 409 BTU/Hr(Max)

Certification

- Safety: CB / NRTL
- EMC: FCC Class “B” / CE / KC
- ePEAT (US Only): Yes
- ErP / Energy Star: Yes (NewErP) / Yes
- ISTA6: Yes (~Sep. 23y, US Suffix Only)
- Carbon Trust: Yes (CO2 Reducing (TBD))

OPS Compatibility

- OPS Type Compatible: No
- OPS Power Built In: No

Software Compatibility

- SuperSign CMS, SuperSign Control / Control+, SuperSign WB, SuperSign Cloud, Mobile CMS, LG ConnectedCare

Connectivity

- Input: HDMI In (3, 3,840 × 2,160 @ 60Hz, HDCP 2.2/1.4), DP In (3,840 × 2,160 @ 60Hz, HDCP 2.2/1.3), RS-232C In (4 Pin Phone-jack), RJ45 (LAN) In, IR In, USB In 2.0 (Type A)
- Output: HDMI Out (3,840 × 2,160 @ 30Hz, Input (HDMI1/2/3/DP)), Audio Out, RS-232C Out (4 Pin Phone-jack), Daisy Chain (Input HDMI, DP / Output HDMI)

Language

- English, French, German, Spanish, Italian, Korean , Chinese(Simplified), Chinese(Original), Portugues(Brazil), Swedish, Finnish, Norwegian, Danish, Russian, Japanese, Portugues(Europe), Dutch, Czech, Greek, Türkiye, Arabic

Accessory

- Basic: Remote Controller(include battery 2ea), Power Cord, QSG, Regulation Book, Phone to RS232C Gender, Cable Holder(2EA), AC Cord Holder (1EA)
- Optional: Slim Wall Mount (WB21LMA/B), Wall Mount (LSW240A/B) Wall Mount Adapter (AM-B220S)

Special Feature

- Tilt (Facedown): Yes (Max 30º degree, 40ºC temperature)