

TP-Link InSight S655I smart home kültéri IP kamera IP67



5MP, 1,44mm F2.0 1/2.7" CMOS, Ethernet (100Mb/s), PoE, beépített mikrofon, beépített hangszóró, forgatható, 2560x1920, 30fps, alakfelismerés, mozgásérzékelő, éjszakai mód, microSD, fehér, H.265+, 480g

Cikkszám: INSIGHT S655I

Ár:

213 660 Ft

Garancia: 3 Év

Kamera

Képérzékelő

1/2.7" Progressive Scan CMOS

Shutter Speed

1/3 to 1/10000 s

Slow Shutter

Yes

Min. szükséges megvilágítás Color: 0.01 Lux; 0 Lux with IR light

Day/Night Mechanism

IR Cut Filter

Day/Night Switch

Unified/ Scheduled/ Auto

LENS

Type

Fixed Focal Lens

Focal Length

1.44 mm

Aperture

F2.0

FOV

Horizontal FOV: 180°, Vertical FOV: 180°, Diagonal FOV:180°

Lens Mount

M12*P0.5

DORI Distance

Detect: 28.8 m (94 ft)

Observe:12 m (39 ft)

Recognize: 5.7 m (19 ft)

Identify: 2.8 m (9 ft)

Fisheye Display

InstallationCeiling Mount; Wall Mount; Pendant Mount^s

- Ceiling Mount:

Fisheye, AR Dewarp, 180 Panorama, 360 Panorama

Cylinder, 2PTZ, 4PTZ, Fisheye + 8PTZ, Fisheye + 3PTZ, 360 Panorama + 8PTZ, 360 Panorama + 6PTZ, 360 Panorama + PTZ

Display Mode

- Wall Mount:

Fisheye, 360 Panoramic Unwrap, 360 Panoramic Unwrap+3PTZ, 360 Panoramic Unwrap+8PTZ, 4PTZ, Fisheye + 3PTZ, Fisheye + 8PTZ

Angle Adjustment (Manual)

Range

N/A

ILLUMINATOR

IR LED

- Quantity: 4
- Range: 30m
- Wavelength: 850nm

White LED

N/A

Illuminator On/Off ControlAuto/Scheduled/Always on/Always off

VIDEO

Max. Resolution

2560 × 1920

- Frame Rate:

50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps

60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps

Main Stream

- Resolution:

2560 × 1920, 2256 × 1696, 2048 × 1536, 1280 × 960

Note:

If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.

If WDR is on, the frame rate only supports up to 15fps.

- Frame Rate:

50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps

60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps

Sub-Stream

- Resolution:

640 × 480, 320 × 240

Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.

If WDR is on, the frame rate only supports up to 15fps.

Bit Rate Control

CBR, VBR

Video Compression

- Main Stream: H.265+/H.265/H.264+/H.264

- Sub-Stream: H.265/H.264

H.264 Type

High Profile

H.264+

Main Stream Supported

H.265 Type

Main Profile

H.265+

Main Stream Supported

Video Bit Rate

- Main Stream: 256 Kbps to 6 Mbps

- Sub-Stream: 64 Kbps to 512 Kbps

Image

- Brightness

- Contrast

- Saturation

- Sharpness

Image Settings

- Exposure

- WDR,

- White Balance

- Prevent Overexposure to Infrared Light

- HLC Adjustable by Client Software

Image Enhancement

BLC/3D DNR/HLC/SmartIR

Wide Dynamic Range

120dB

SNR

≥ 52 dB

Image Parameters Switch

Yes

Privacy Mask

Up to 4 Masks

ROI

1 Region

OSD Setting

Yes

Hang

Hangkommunikáció

Two-Way Audio

Hangbemenet

Yes

Hangkimenet

Yes

Hangtömrítés

Yes

Audio Sampling Rate

8KHz

Environment Noise Filtering

Yes

Audio Bit Rate

64 Kbps(G.711 alaw)

Hálózat

Szabvány

TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP, UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP

ONVIF

Yes

API

Open Network Video Interface (Profile S/T/G)

Simultaneous Live

3 Main Streams & 3 Sub-Streams

View

Client

Utility, VIGI App, Web UI, VIGI VMS, VIGI Cloud VMS

- Google Chrome® 57 and above

- Firefox® 52 and above

- Safari® 11 and above

Web Browser

	• Microsoft® Edge 91 and above
Cloud	Yes
Biztonság	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
Figyelmeztetési és eseménykezelési vezérlés	
	• Intrusion Detection • Line-Crossing Detection
Smart Event	• Region Entering Detection • Region Exiting Detection • Abnormal Sound Detection • Motion Detection
Basic Event	• Video Tampering Detection • Exception (Illegal Login) • Memory Card Video Recording
Alarm Linkage	• Message Push • Audible Warning
Linkage Method	N/A
	• Message Push
Output Notification	• Email Alarm • Upload Capture to FTP
Fizikai kezelőfelület	
Hálózati csatlakozás	1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE
Alarm	N/A
Reset Button	Yes
Power	DC Power Port
On-board Storage	Built-In Memory Card Slot, Support MicroSD Card, up to 512 GB [§]
Built-in Microphone	Yes; Records Anything Going on within a 15-ft Radius of the Camera
Built-in Speaker	Yes
Audio	N/A
Általános	
Operating Temperature	-30-60 °C
Storage Temperature	-40-60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing)
	• VIGI Network Camera • Quick Start Guide • Waterproof Cable Attachments • Mounting Accessories
Csomagolás tartalma	
Material	Metal
Net Weight	• 0.44 Kg (without Mounting Accessories) • 0.48 Kg (with Mounting Accessories)
Power Supply	• 12V DC ± 5%, Max. 11.76 W, 5.5mm Coaxial Power Plug • PoE: 802.3af/at, class 0, Max. 12.14W
Protection	IP67 Weatherproof, IK10 Vandal Proof
Product Dimensions (L x W x H)	5.2 × 5.2 × 2.2 in (132 × 132 × 56mm)
Certifications	CE; NTRA; KC; FCC; VCCI; BSMI; ONVIF

alakfelismerés	Van
beépített hangszóró	mono
érzékelő felbontása	5MP
látószög	180°
smart home	Van
tömeg	480
videó felbontása	2560x1920
Gyártó	TP-Link

beépített mikrofon	Van
cikknév kiegészítés	IP67
csatlakozó	Ethernet (100Mb/s)
éjszakai mód	Van
érzékelő típusa	1,44mm F2.0 1/2.7" CMOS
forgatható	Van
kamera rögzítés típusa	falra és mennyezetre rögzíthető
memóriakártya foglalat	microSD
mozgásérzékelő	Van
PoE	Van
rögzítési formátumok	H.265+
rögzítési sebesség	30
szín	fehér