

TP-Link EAP650-Desktop AX3000 Dual-Band Wi-Fi PoE
access point



2976Mb/s, IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), LAN (1Gb/s): 4 port, RJ11: 1db, antennák száma: 3db, 4,7dBi, Mesh Wi-Fi, energiafelhasználás: 17,3W, fehér

Cikkszám: EAP650-DESKTOP

Ár:

81 280 Ft

Garancia: 5 Év

HARDWARE FEATURES

Interface	4× 1Gbps Ethernet Ports + 1× FXS Port (One Ethernet port supports PoE Out: 802.3at/af output at 802.3bt input, 802.3af class 2 output at 802.3at input)
Button	• Reset • LED
Power Supply	802.3 af/at/bt PoE or 12V/1.5A DC *PoE Out requires 802.3at/bt PoE power supply
Power Consumption	17.3W (PoE Out Off)
Weight	452g (excluding mounting base)
Dimensions (W x D x H)	6.9 × 5.5 × 1.3 in (175 × 140 × 33 mm)
Antenna Type	Internal Omni • 2.4 GHz: 2× 5 dBi • 5 GHz: 3× 4.7 dBi
Range	140?(1500 ft2)*
Mounting	Desktop / Wall mouting (Kits included)

WIRELESS FEATURES

Concurrent Clients	250+*
Wireless Standards	IEEE 802.11 a/b/g/n/ac/ax
Frequency	2.4 GHz and 5 GHz • 5 GHz: 2402 Mbps[†] • 2.4 GHz: 574 Mbps • 2×2 (2.4G & 5G) MU-MIMO[‡] • HE160 (160 MHz Bandwidth)[‡] • OFDMA[‡] • Seamless Roaming[§] • Multiple SSIDs (16 SSIDs, 8 on each band) • Enable/Disable SSID Broadcast • Enable/Disable Wireless Radio • Guest Network • Automatic Channel Assignment • Beamforming
Wireless Functions	• Rate Limit (Based on SSID/Client) • Band Steering • Load Balance • Airtime Fairness

	• Transmit Power Control (Adjust Transmit Power on dBm) • QoS (WMM) • RADIUS Accounting • MAC Authentication • Reboot Schedule • Wireless Schedule and Statistics • Static IP/Dynamic IP • Captive Portal Authentication^s • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients • VLAN • Rogue AP Detection • 802.1X Support • WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise • CE: <20 dBm(2.4 GHz, EIRP) <23 dBm(5 GHz, band1 & band2, EIRP) <29 dBm(5 GHz, band3, EIRP)
Wireless Security	
Transmission Power	• FCC: <26 dBm (2.4 GHz) <27 dBm (5 GHz)
MANAGEMENT	
Omada App	Yes
Centralized Management	• Omada Hardware Controller • Omada Software Controller • Omada Cloud-Based Controller
Cloud Access	Yes.
Email Alerts	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1, v2c, v3
System Logging Local/Remote Syslog	System Log
SSH	Yes
Web-based Management	Yes
Zero-Touch Provisioning	Yes.Reauire the use of Omada Cloud-Based controller
OTHERS	
Certification	CE, FCC, RoHS, IC • EAP650-Desktop
Package Contents	• Desktop/Wall Mounting Kit • Installation Guide
System Requirements	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux • Operating Temperature: 0-40 ? (32-104 ?) • Storage Temperature: -40-70 ? (-40-158 ?) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing
Environment	

Dual-Band	Van
energiafelhasználás	17.3
LAN (1Gb/s)	4
Mesh Wi-Fi	Van
PoE port	2
tömeg	452
Wi-Fi átviteli sebesség	2976

Wi-Fi jeltípus	IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6)
Wi-Fi titkosítás	WPA3;WPA3-Enterprise;WPA2-PSK;WPA2-Enterprise
Gyártó	TP-Link
antenna nyeresége	4.7
antenna típusa	belső
antennák száma	3
PoE	Van
RJ11	1
WI-FI	Van
szín	fehér