

TP-Link Tapo C501GW smart home kültéri IP kamera 4G/LTE IP66



2MP, 3,17mm F1.65 1/2.9" CMOS, Ethernet (100Mb/s), 4G/LTE, PoE, beépített mikrofon, beépített hangszóró, forgatható, 1920x1080, 30fps, alakfelismerés, mozgásérzékelő, éjszakai mód, microSD, fehér, H.264

Cikkszám: TAPO C501GW

Ár:

69 010 Ft

Garancia: 2 Év

??????

??1/2.9" CMOS Sensor

Focal Length: 3.17 mm

????????

Aperture: F1.65

Field of View: 122° (Diagonal), 105°(Horizontal), 59°(Vertical)

Motion Range

Pan Mechanical Range: 340° (360° Pan Coverage)

Tilt Mechanical Range: 60° (130° Tilt Coverage)

Night Vision

850 nm IR LED (98 ft / 29.9 m), starlight color night vision

1× DC Port

1× Ethernet Port, PoE

Interface & Button

1× RESET Button

1× microSD Card Slot (Up to 512GB)

1× Nano-SIM Card Slot

VIDEO & AUDIO

Maximum Resolution 1920 × 1080 px

Frame Rate 30 fps

Video Compression H.264

Live View Yes

Audio Input & Output Built-in Microphone and Speaker

Audio CommunicationTwo-Way Audio with Noise Cancellation

Siren Volume 99 dB (Level measured at 4-inch/10-cm distance)

STORAGE

Local Storage MicroSD Card Slot on Camera (Up to 512 GB)

General Information about using microSD Cards >

Cloud StorageTapo Care Cloud Storage Services (Subscription required)

DETECTION and NOTIFICATIONS

Motion Detection

Person Detection

Pet Detection

Vehicle Detection

AI Detection

Tamper Detection

Line-Crossing Detection

Meow Detection

Bark Detection

Glass-Breaking Detection

Activity Zones

Yes

Output Notification

System Notification

System Notification with Snapshot (Tapo Care Services)

?????

Network Connectivity3G/4G LTE/LAN Cable

RTSPYes

ONVIFYes

4G

FrequencyLTE-FDD: B1/3/5/7/8/20/28, LTE-TDD: B38/40/41

??????????

Power Source12V DC Power Adapter
PoE: 802.3 af/at

Input Voltage100-240 V, 50/60 Hz

Output VoltageDC Power:12V, 1A

???? ??????????????

Smart IntegrationGoogle Assistant, Amazon Alexa

Weather ResistanceIP66

System RequirementsTapo App: iOS 9.0 or higher, Andriod 4.4 or higher

Ceiling-Mounted

Mounting OptionsWall-Mounted

Pole-Mounted (Pole-Mounting loops required but not included)

????? ?????????????? ??? ??????-30?~60?

Storage Temperature-40?~60?

????? ?????????? ??? ??????10%~90% RH, Non-condensing

Storage Humidity0~90% RH, Non-condensing

Camera Dimensions: 5.15× 3.31×4.57 in (130. 8× 84.0 × 116.1 mm)

DimensionsCamera Dimensions with included antennas and bracket

5.5 × 4.03 × 9.22 in (139.8 × 102.3 × 234.2 mm)

Tapo C501GW Camera

Detachable Antenna

DC Power Adapter

Mounting Template

Mounting Bracket

????????????? ?? ??????Mounting Anchors

Bracket Screws

Mounting Screws

Waterproof Seal

Waterproof Cable Attachments

Quick Start Guide

CertificationsCE,NTRA,RCM,VCCI,NCC,BSMI,ROH

4G/LTE	Van
alakfelismerés	Van
beépített hangszóró	mono
érzékelő felbontása	2MP
látószög	122°
smart home	Van
videó felbontása	1920x1080
Gyártó	TP-Link
beépített mikrofon	Van
cikknév kiegészítés	IP66
csatlakozó	Ethernet (100Mb/s)
döntési szög	60

éjszakai mód	Van
érzékelő típusa	3,17mm F1.65 1/2.9" CMOS
forgatási szög	340
forgatható	Van
kamera rögzítés típusa	falra rögzíthető
memóriakártya foglalat	microSD
mozgásérzékelő	Van
PoE	Van
rögzítési formátumok	H.264
rögzítési sebesség	30
szín	fehér