

Zyxel USG FLEX 500H PoE rack tűzfal

LAN (1Gb/s): 8 port, LAN (2,5Gb/s): 4 port, USB3.0, VPN csatomák száma:
300db, tűzfal, energiafelhasználás: 68W, piros-szürke

Cikkszám: USGFLEX500H-EU0101F

Ár:

506 500 Ft



Garancia: 5 Év
Hardware Specifications

Interface ports

- 2 x 2.5-GbE Ethernet
- 2 x 2.5-GbE/PoE Ethernet (802.3at, total 30W)
- 8 x 1-GbE Ethernet
- USB 3.0 ports
- 1
- Console port
- Yes (RJ-45)
- Rack-mountable
- Yes
- Fanless
-

System Capacity & Performance*1

SPI firewall throughput (Mbps)*2

10,000

VPN throughput (Mbps)*3

2,000

IPS throughput (Mbps)*4

3,500

Anti-Malware throughput (Mbps)*4

2,500

UTM throughput (Anti-malware & IPS, Mbps)*4

2,500

Max. TCP concurrent sessions* ⁵	1,000,000
Max. concurrent IPsec VPN tunnels* ⁶	300
Recommended gateway-to-gateway IPsec VPN tunnels	150
Concurrent SSL VPN users	150
VLAN interface	64
Max. Concurrent devices logins* ⁷	300
Security Service* ⁸	
Anti-Malware	Yes
IPS	Yes
Application Patrol	Yes
Web filtering	Yes
Reputation Filter	Yes
SecuReporter	Yes
Sandboxing	Yes
Device Insight	Yes
Secure WiFi* ⁹	Yes
Key Features	
VPN	
IKEv2, IPsec, SSL	
SSL (HTTPS) inspection	Yes
Two-Factor Authentication	Yes

Nebula Centralized Management

Yes

Power Requirements

Power input

19V DC, 4.736A

Max. power consumption (Watt Max.)

68

Heat dissipation (BTU/hr)

211.3

PoE power budget (watt max.)

30

Physical Specifications

Item

Dimensions (WxDxH)(mm/in.): 300 x 182 x 43.5/11.81 x 7.17 x 1.71

Weight (kg/lb.): 1.64/3.62

Packing

Dimensions (WxDxH)(mm/in.): 350 x 149 x 244/13.78 x 5.87 x 9.61

Weight (kg/lb.): 2.93/6.46

Included accessories

Power adapter & Power cord

RJ-45 - RS-232 cable for console connection

Rack mounting kit

Environmental Specifications

Operating

Temperature: 0°C to 40°C / 32°F to 104°F

Humidity: 10% to 90% (non-condensing)

Storage

Temperature: -30°C to 70°C / -22°F to 158°F

Humidity: 10% to 90%(non-condensing)

MTBF (hr)

40°C/ 346653.298 hr

25°C/ 491775.8384 hr

Acoustic noise

16.86dBA on < 25degC Operating Temperature, 43.76dBA on full FAN speed

Certifications

EMC

FCC Part 15 (Class A)

CE EMC (Class A)
RCM (Class A)
BSMI
Safety
LVD (EN62368-1)
BSMI

energiafelhasználás	68
LAN (1Gb/s)	8
LAN (2,5Gb/s)	4
PoE port	2
rack	Van
tömeg	1640
USB3.0	1
VPN csatornák száma	300
Gyártó	Zyxel
PoE	Van
tűzfal	Van
szín	piros-szürke