

Zyxel USG FLEX 500H PoE rack tűzfal + 1év Security Bundle

LAN (1Gb/s): 8 port, LAN (2,5Gb/s): 4 port, USB3.0, VPN csatomák száma: 300db, tűzfal, energiafelhasználás: 68W, piros-szürke

Cikkszám: USGFLEX500H-EU0102F

Ár:



606 840 Ft

Garancia: 5 Év
Hardware Specifications

- Interface ports
- 2 x 2.5-GbE Ethernet
- 2 x 2.5-GbE/PoE Ethernet (802.3at, total 30W)
- 8 x 1-GbE Ethernet
- USB 3.0 ports
- 1
- Console port
- Yes (RJ-45)
- Rack-mountable
- Yes
- Fanless
-
- System Capacity & Performance*1

- SPI firewall throughput (Mbps)*2
- 10,000
- VPN throughput (Mbps)*3
- 2,000
- IPS throughput (Mbps)*4
- 3,500
- Anti-Malware throughput (Mbps)*4
- 2,500
- UTM throughput (Anti-malware & IPS, Mbps)*4

2,500

Max. TCP concurrent sessions*⁵

1,000,000

Max. concurrent IPsec VPN tunnels*⁶

300

Recommended gateway-to-gateway IPsec VPN tunnels

150

Concurrent SSL VPN users

150

VLAN interface

64

Max. Concurrent devices logins*⁷

300

Security Service*⁸

Anti-Malware

Yes

IPS

Yes

Application Patrol

Yes

Web filtering

Yes

Reputation Filter

Yes

SecuReporter

Yes

Sandboxing

Yes

Device Insight

Yes

Secure WiFi*⁹

Yes

Key Features

VPN

IKEv2, IPsec, SSL

SSL (HTTPS) inspection

Yes

Two-Factor Authentication

Yes

Nebula Centralized Management

Yes

Power Requirements

Power input

19V DC, 4.736A

Max. power consumption (Watt Max.)

68

Heat dissipation (BTU/hr)

211.3

PoE power budget (watt max.)

30

Physical Specifications

Item

Dimensions (WxDxH)(mm/in.): 300 x 182 x 43.5/11.81 x 7.17 x 1.71

Weight (kg/lb.): 1.64/3.62

Packing

Dimensions (WxDxH)(mm/in.): 350 x 149 x 244/13.78 x 5.87 x 9.61

Weight (kg/lb.): 2.93/6.46

Included accessories

Power adapter & Power cord

RJ-45 - RS-232 cable for console connection

Rack mounting kit

Environmental Specifications

Operating

Temperature: 0°C to 40°C / 32°F to 104°F

Humidity: 10% to 90% (non-condensing)

Storage

Temperature: -30°C to 70°C / -22°F to 158°F

Humidity: 10% to 90%(non-condensing)

MTBF (hr)

40°C/ 346653.298 hr

25°C/ 491775.8384 hr

Acoustic noise

16.86dBA on < 25degC Operating Temperature, 43.76dBA on full FAN speed

Certifications

EMC

FCC Part 15 (Class A)
CE EMC (Class A)
RCM (Class A)
BSMI
Safety
LVD (EN62368-1)
BSMI

energiafelhasználás	68
LAN (1Gb/s)	8
LAN (2,5Gb/s)	4
PoE port	2
rack	Van
tömeg	1640
USB3.0	1
VPN csatornák száma	300
Gyártó	Zyxel
cikknév kiegészítés	+ 1év Security Bundle
PoE	Van
tűzfal	Van
szín	piros-szürke