Szanex Computer webshop

Szanex Bt.
Cégjegyzék szám: 05-06-005646
Adószám: 21302541-2-05

3700 Kazincbarcika, Dózsa Gy. út 24.
szanex@szanex.hu
(48) 512-880

StarTech USB-A 3.0 -> VGA DVI-I M/F adapter 0.15m fekete

Cikkszám: USB32DVIPRO

Ár:

62 790 Ft

The USB32DVIPRO USB 3.0 to DVI Adapter turns an available USB 3.0 port into a DVI output, with high resolution 2048x1152 video support - a convenient external video solution that makes it easy to add multi-monitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0).

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter functions as a external graphics card to deliver smooth, high-resolution content to your DVI or VGA-capable display (DVI to VGA Adapter included). The adapter can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:
CPU: Quad Core 2.4GHz or Higher (i5 recommended)
RAM: 4GB or higher

The StarTech.com Advantage

- SuperSpeed USB 3.0 to DVI conversion provides added bandwidth, for smooth high-resolution video content
- External USB-Powered device provides the simplest way to add additional graphics capability to your system, without opening the case or voiding system warranties

Audio	Yes
Chipset ID	DisplayLink - DL3100
Memory	512MB DDR2 SDRAM
Output Signal	DVI-I (DVI Digital/Analog)
USB Pass-Through	No

Performance

General Specifications	This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a Trigger or Fresco family chipset.
Maximum Analog Resolutions	2048x1152
Maximum Digital Resolutions	2048x1152
Note	If using OS X 10.8, Apple update 10.8.3 must be installed before installing DisplayLink software. 10.8.3 fixes several serious OS X bugs exposed when DisplayLink software is installed.
Supported Resolutions	Widescreen(16/32 bit): 2048x1152, 1920x1200, 1920x1080, 1680x1050, 1366x768, 1280x800, 1280x768, 1280x720

Standard(16/32 bit):
1600x1200, 1400x1050, 1280x1024, 1024x768, 800x600, 640X480

Wide Screen Supported	Yes

Connector(s)

Connector A	1 - USB 3.0 A (9 pin; SuperSpeed) Male
Connector B	1 - DVI-I (29 pin) Female

Software

OS Compatibility	Windows® 10 (32/64), 8/8.1 (32/64), 7 (32/64), Vista (32/64), XP (32/64), 2000 (Aero 3D interface supported)
	Apple® OSX El Capitan (10.11), Yosemite (10.10), Mavericks (10.9) Mountain Lion (10.8), Lion (10.7), Snow Leopard (10.6)

Special Notes / Requirements

Note	Connect a maximum of five USB32DVIPRO adapters on a single PC - See manual for system requirements
System and Cable Requirements	1~2 USB Displays Office Application: CPU: i3 Dual core 2.8GHz RAM: 2GB or higher
	Full HD Video: CPU: Quad Core 2.4GHz or Higher (i5 recommended) RAM: 4GB or higher

Power

Power Source	USB-Powered

Environmental

Humidity	<85% RH Non-Condensing
Operating Temperature	10°C to 40°C (50°F to 104°F)
Storage Temperature	-10°C to 80°C (14°F to 167°F)

Physical Characteristics

Color	Black
Enclosure Type	Plastic
Product Height	0.6 in [15.5 mm]
Product Length	3.1 in [78 mm]
Product Weight	10.6 oz [300 g]
Product Width	1.7 in [43.5 mm]

Packaging Information

Shipping (Package) Weight	0.5 lb [0.2 kg]

What's in the Box

Included in Package	1 - USB 3.0 to DVI Adapter
	1 - DVI to VGA Adapter
	1 - Driver CD
	1 - Installation guide

Gyártó	StarTech