

Asus PRIME A520M-K desktop alaplap microATX



AMD, A520, sAM4, 2db, 4600MHz, DDR4, PCI-E x16: 1db, PCI-E x1: 2db, SATA3: 4db, M.2: 1db, 1Gb/s, D-Sub, HDMI kimenet

Cikkszám: PRIME A520M-K

Ár:

39 380 Ft

Garancia: 3 Év

- CPU
Build in AMD AM4 Socket Processors *
* Refer to www.asus.com for CPU support list
- Chipset
AMD A520
- Memory
2 x DIMM, Max. 64GB, DDR4
4600(O.C.)/4400(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3333(O.C.)/3200/3000/2800/2666/2400/2133 MHz Un-buffered Memory *
Dual Channel Memory Architecture
ECC Memory (ECC mode) support varies by CPU.
* Refer to www.asus.com for the Memory QVL (Qualified Vendors Lists).
* The maximum memory frequency supported varies by processor.
- Graphic
1 x D-Sub
1 x HDMI 2.1(4K@60HZ)
- Expansion Slots
3rd Gen AMD Ryzen™ and 3rd Gen AMD Ryzen™ with Radeon™ Graphics Processors
1 x PCIe 3.0 x16 (x16 mode)
AMD A520 Chipset
2 x PCIe 3.0 x1
- Storage
Total supports 1 x M.2 slot(s) and 4 x SATA 6Gb/s ports
3rd Gen AMD Ryzen™ and 3rd Gen AMD Ryzen™ with Radeon™ Graphics Processors :
1 x M.2 Socket 3, with M Key, Type 2242/2260/2280 (PCIe 3.0 x4 and SATA modes) storage devices support
AMD A520 Chipset :
4 x SATA 6Gb/s port(s),
Support Raid 0, 1, 10
- LAN
Realtek RTL8111H 1Gb Ethernet
ASUS LANGuard
- Audio
Realtek ALC887 7.1 Surround Sound High Definition Audio CODEC *
- Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback
Audio Feature :
- Audio Shielding
- Dedicated audio PCB layers
* Choose the chassis with HD audio module in front panel to support 8-channel audio output.
- USB Ports
Rear USB Port (Total 6)
4 x USB 3.2 Gen 1 port(s)(4 x Type-A)
2 x USB 2.0 port(s)(2 x Type-A)
Front USB Port (Total 6)
2 x USB 3.2 Gen 1 port(s)(2 x Type-A)
4 x USB 2.0 port(s)(4 x Type-A)
- Software Features
ASUS Exclusive Software

- Armoury Crate
- AI Suite 3
 - Performance and Power Saving Utility
- TurboV EVO
- EPU
- Digi+ VRM
- Fan Xpert
 - EZ update
- ASUS CPU-Z
- AI Charger
- DAEMON Tools
- Norton Anti-virus software (Free Trial for 60 days)
- WinRAR
- UEFI BIOS
- ASUS EZ DIY
 - ASUS CrashFree BIOS 3
 - ASUS EZ Flash 3
 - ASUS UEFI BIOS EZ Mode
- ASUS Special Features
- ASUS 5X PROTECTION III
 - ASUS DIGI+ VRM
 - ASUS LANGuard
 - ASUS Overvoltage Protection
 - ASUS SafeSlot Core
 - ASUS Stainless-Steel Back I/O
- ASUS Q-Design
 - ASUS Q-DIMM
 - ASUS Q-Slot
- ASUS Thermal Solution
 - Aluminum heatsink design
- Back I/O Ports
 - 1 x PS/2 keyboard/mouse combo port(s)
 - 1 x D-Sub
 - 1 x HDMI
 - 1 x LAN (RJ45) port(s)
 - 4 x USB 3.2 Gen 1 (blue) Type-A
 - 2 x USB 2.0
 - 3 x Audio jack(s)
- Internal I/O Ports
 - 1 x CPU Fan connector(s)
 - 1 x Chassis Fan connector(s)
 - 1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s)
 - 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s)
 - 1 x M.2 Socket 3 with M key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 x 4 mode)
 - 1 x SPI TPM header
 - 4 x SATA 6Gb/s connector(s)
 - 1 x S/PDIF out header(s)
 - 1 x 24-pin EATX Power connector(s)
 - 1 x 8-pin EATX 12V Power connectors
 - 1 x Front panel audio connector(s) (AAFP)
 - 1 x Clear CMOS jumper(s)
 - 1 x System panel connector
 - 1 x COM port header
 - 1 x Speaker connector
- Accessories
 - User's manual
 - I/O Shield
 - 2 x SATA 6Gb/s cable(s)
 - 1 x Supporting DVD
 - 1 x M.2 SSD screw package(s)
- BIOS
 - 256 Mb Flash ROM, UEFI AMI BIOS
- Manageability
 - WOL by PME, PXE
- Operating System
 - Windows® 10 64-bit
- Form Factor
 - mATX Form Factor
 - 8.9 inch x 8.7 inch (22.6 cm x 22.1 cm)

