

TP-Link Vigī NVR4064H hálózati video rögzítő NVR

beépíthető meghajtók száma: 4db, 2,5" / 3,5", SATA3, USB2.0, USB3.0:
1db, eSATA, D-Sub: 1db, HDMI kimenet: 2db, LAN (1Gb/s): 2db, 64-
channel, szürke

Cikkszám: VIGI NVR4064H

Ár:

693 300 Ft



Garancia: 3 Év

Video and Audio

IP Video Input	64-Channel
Incoming	Default: 260Mbps
Bandwidth	Extended Bandwidth Mode: 320Mbps
Outgoing	Default: 180Mbps
Bandwidth	Extended Bandwidth Mode: 320Mbps
HDMI Output	1 Channel, Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1680x1050/60Hz,
Resolution	1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
VGA Output	1 Channel, Resolution: 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz,
Resolution	1280x1024/60Hz, 1280x720/60Hz
Video Output	HDMI/VGA Independent Output
Mode	
Multi-View	1,4,6,8,9,16,25,32,36,49,64
Display	

DECODING

Audio Compression	G.711A/G.711U/G.726
Video Compression	H.265+/H.265/ H.264+/H.264
Record Resolution	8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	16-Channel† • 25fps: 16-ch@2MP?32-ch@720P?64-ch@D1

Capability

- 30fps:
4-ch@8MP?6-ch@5MP?8-ch@4MP

Record Management

Record Mode	• Manual Recording • Scheduling Recording • Motion Detection Recording • Instant Playback
Playback Mode	• Regular Playback • Tag Playback • Event Playback
Backup Mode	• Regular Backup • Video Clip Backup • Play • Pause • Stop • Fast Forward • Fast Backward

Playback Function	• Play By Frame • Full Screen • Video Clip • Export Clip • Digital Zoom • Lock Recording • Audio On/Off
NETWORK	
Protocol	UPnP (Plug and Play), NTP (Network Timing), SMTP, DNS, TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, RTSP, SSL/TLS, RTP, IPv4, ARP
Mobile Phone Access	Android, iOS
Web Browser	Chrome (57+), Firefox (52+), Edge (91+)
Interoperability	ONVIF Profile S/T/G, CGI
External Interface	
Network Interface	2, RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface
USB Interface	2 Front USB 2.0 Ports, 1 Rear USB 3.0 Port
Audio Interface	1-ch RCA Input; 1-ch RCA Output
Alarm In/Out	16/4
Serial Interface	1, RS232
Power	1× AC Jack
Reset Button	1
Speaker	N/A
eSATA	1
HDMI	2
VGA	1
HARD DISK	
SATA	4 SATA Interfaces
Capacity	Up to 16 TB Capacity for Each HDD*
Alarm	
	• Motion Detection • Video Tampering • Scene Change Detection • Line-Crossing Detection • Intrusion Detection • Region Entering Detection • Region Exiting Detection • Loitering Detection • Object Abandoned/Removal Detection • Vehicle Detection • Human Detection • Abnormal Sound Detection • Smart Frame
General Alarm	Note: The alarm function requires the use of a camera.
	• Video Loss • Offline and IP Conflict
Anomaly Alarm	• Disk Exception • Login Exception • Fan Exception
	Note: The alarm function requires the use of a camera.
	• Recording • White Light Alarm
Alarm Linkage	• Buzzer • Log • Audible Alarm
	Note: The alarm function requires the use of a camera.
GENERAL	
Storage Temperature	-40~70 °C
Storage Humidity	10%~90% RH Non-Condensing
	• VIGI Network Video Recorder • Mouse • Installation Guide

Package Contents	• Power Cord • HDD Power Cables • HDD Data Cables • Terminal Blocks • Mounting Brackets • Screws • Rubber Feet
Working Temperature	• NVR: -10-55 °C
Working Humidity	10%~90% RH Non-Condensing
Dimensions(W X D X H)	440 × 330 × 44 mm
External Power Supply	100-240 VAC, 50 to 60HZ, 1.5A
Net Weight	4.0 Kg [#]
Gross Weight	5.0 Kg [#]
Power Supply	100-240 VAC, 50 to 60Hz, 1.5A
Power Consumption	• 6.95 W (Without Disk) • 48.38 W (With Disk)
Certifications	CE, NTRA, KC, HDMI, FCC, IC, VCCI, BSMI, ONVIF

audio kimenet	1
cikk kiegészítés	64-channel
LAN (1Gb/s)	2
Gyártó	TP-Link
beépítési méret	2,5" / 3,5"
beépíthető meghajtók száma	4
belső csatlakozó	SATA3
D-Sub	1
eSATA	1
fogyasztás	48,38
tömeg	4 kg
USB2.0	2 db
USB3.0	1
szín	szürke