

TP-Link EAP725-Wall BE5000 Dual-Band Wi-Fi PoE access point



5000Mb/s, IEEE 802.11be (Wi-Fi 7), LAN (1Gb/s): 2 port, LAN (2,5Gb/s): 2 port, antennák száma: 4db, 5dBi, Mesh Wi-Fi, fehér

Cikkszám: EAP725-WALL

Ár:

101 120 Ft

Garancia: 5 Év

HARDWARE FEATURES

Interface	• Uplink: 1× 2.5G Ethernet Port • Downlink: 1× 2.5G Ethernet Port + 2× Gigabit Ethernet Ports
	(The 2.5G port supports PoE pass-through. The PoE pass-through feature requires 802.3at/bt input. If the power consumption of the AP's downstream device exceeds 7W, the AP needs an 802.3bt input.)
Physical Security Lock	No
Button	Reset, LED
Power Supply	802.3at/bt PoE
Power	• 802.3bt: 17W (PoE Out support 15.4W)
Consumption	• 802.3at: 17W (PoE Out support 7W)
Dimensions	143 × 86 × 40 mm (5.6 × 3.4 × 1.6 in)
Antenna	4× Internal Antennas
	• 2.4 GHz: 2× 4 dBi • 5 GHz: 2× 5 dBi
Mounting	Wall Mounting (Kits included)

WIRELESS FEATURES

Coverage	50 ? (600 ft2)**
Concurrent Clients	250+ [§]
Wireless Standards	IEEE 802.11 a/b/g/n/ac/ax/be
Frequency	2.4 GHz and 5 GHz
Signal Rate	• 5 GHz: Up to 4324 Mbps • 2.4 GHz: Up to 688 Mbps
	• 16 SSIDs (Up to 8 SSIDs on each band) • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control (Adjust Transmit Power on dBm) • QoS(WMM) • Seamless Roaming[?] • Beamforming • Rate Limit (Based on SSID/Client)
Wireless Functions	• Load Balance • Airtime Fairness • Band Steering • Reboot Schedule

	• Wireless Schedule • RADIUS Accounting • MAC Authentication • Wireless Statistics • Static IP/Dynamic IP • Captive Portal Authentication? • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients • VLAN • Rogue AP Detection • WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise
Wireless Security	
Transmission Power	< 22 dBm (2.4 GHz) < 22 dBm (5 GHz, band 1 & band 2 & band 3 & band 4)
MANAGEMENT	
Omada App	Yes
Centralized Management	• Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller • Omada Cloud-Based Controller
Cloud Access	Yes. Requiring the use of OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller.
Email Alerts	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1, v2c, v3
System Logging	System Log
Local/Remote Syslog	
SSH	Yes
Web-based Management	Yes
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
Zero-Touch Provisioning	Yes. Requiring the use of Omada Cloud-Based Controller.
OTHERS	
Certification	FCC, RoHS
Package Contents	• BE5000 Wall Plate Wi-Fi 7 Access Point • Installation Guide • Mounting Kits
System Requirements	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows 11, Linux
Environment	• Operating Temperature: 0–40 ° (32–104 °) • Storage Temperature: -40–70 ° (-40–158 °) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

antenna nyeresége	5
Dual-Band	Van
LAN (1Gb/s)	2
LAN (2,5Gb/s)	2
Mesh Wi-Fi	Van
PoE port	2
Wi-Fi	Van
Wi-Fi átviteli sebesség	5000

Wi-Fi jeltípus	IEEE 802.11be (Wi-Fi 7)
Wi-Fi titkosítás	WPA3;WPA3-Enterprise;WPA2-PSK;WPA2-Enterprise
Gyártó	TP-Link
antenna típusa	belső
antennák száma	4
PoE	Van
szín	fehér