

StarTech 2-Port Serial Device Server

Cikkszám: NETRS2322P

Ár:

152 400 Ft



This 2-port serial device server is a cost-effective way to remotely connect to and manage two serial devices over your typical IP network. The device server integrates two RS232 ports into a rugged metal housing with an extended operating temperature range, so it's perfect for factory and industrial settings.

Flexible installation, in a range of environments

If you're looking for a reliable serial-over-IP control solution, then this device server can help. With a rugged metal housing and an extended operating temperature range, you can rest assured that the device server can deliver the reliable performance you need, even in harsh environments.

Plus, it features two integrated mounting brackets, so you can mount the device server to a surface or a wall as needed, for out-of-the-way installations.

Backup power keeps your devices connected

With redundant power input, this dual-port serial device server ensures seamless operation, even in the event of power dips or failures. It features a wide-range, terminal block power input (9~36V DC), and includes a universal power adapter.

Because it features two power inputs, if you experience a power disruption the device server automatically switches to its secondary power source. With redundant power input, the device server remains operational if one of the power sources fails, so you can continue to connect to and manage your serial devices when needed.

Hardware

| | |
|--------------------|---|
| Industry Standards | IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX |
| Interface | Serial |
| Ports | 2 |

Performance

| | |
|---------------------------|------------------------------|
| Auto MDIX | Yes |
| Auto-Negotiation | Yes |
| Compatible Networks | 10/100 Mbps |
| Data Bits | 7, 8 |
| Flow Control | XON/XOFF, RTS/CTS, None |
| Full Duplex Support | Yes |
| Isolation | 2500 Vrms |
| Max Baud Rate | 460.8 Kbps |
| Parity | None, Even, Odd, Space, Mark |
| Remote Management Ability | Yes |

| | |
|---------------------|--|
| Serial Protocol | RS-232 |
| Supported Protocols | ICMP, IP, TCP, UDP, DHCP, BOOTP, Telnet |
| | ESD (Electrostatic Discharge) Protection: |
| Surge Protection | 15kV Human Body Model (HBM) 15kV IEC1000-4-2 Air 8kV IEC1000-4-2 Contact |

Connector(s)

| | |
|-------------------|---|
| Connector Type(s) | 2 - DB-9 (9 pin; D-Sub) Male 1 - RJ-45 Female 1 - Terminal Block (2 Wire) |
|-------------------|---|

Software

Virtual COM software - Windows® Only:
Windows 10 (32-bit or 64-bit), 8 / 8.1 (32-bit or 64-bit), 7 (32-bit or 64-bit), Vista (32-bit or 64-bit)
Windows Server® 2012, 2008 R2

OS Compatibility **Note:** The device server’s hardware is compatible with Mac OS and Linux®; however, the provided Virtual COM software is not compatible with these operating systems.
When used with a Mac or Linux operating system, the device server can only be configured using the Web-GUI.

Indicators

| | |
|----------------|---|
| LED Indicators | 2 - Status 2 - Port 1 2 - Port 2 1 - 10/100Mbps LAN 1 - Link / Activity |
|----------------|---|

Power

| | |
|---------------------|---------------------|
| Center Tip Polarity | Positive |
| Input Current | 1.5 A |
| Input Voltage | 100 ~ 240 AC |
| Output Current | 3 A |
| Output Voltage | 12 DC |
| Power Consumption | 36 W Max |
| Power Source | AC Adapter Included |

Environmental

| | |
|-----------------------|---------------------------------|
| Humidity | 20~80% RH (Non-condensing) |
| Operating Temperature | 0°C to 85°C (32°F to 185°F) |
| Storage Temperature | -45°C to 130°C (-49°F to 266°F) |

Physical Characteristics

| | |
|----------------|-----------------|
| Color | Black |
| Enclosure Type | Steel |
| Product Height | 0.9 in [23 mm] |
| Product Length | 4.4 in [112 mm] |
| Product Weight | 11.3 oz [320 g] |
| Product Width | 3.2 in [81 mm] |

Packaging Information

| | |
|---------------------------|-----------------|
| Shipping (Package) Weight | 24.2 oz [685 g] |
|---------------------------|-----------------|

What's in the Box

| | |
|---------------------|---|
| Included in Package | 1 - 2-port serial device server 1 - terminal block (2-wire) 1 - universal power adapter (NA/EU/UK/AU) 1 - software CD 1 - quick start guide |
|---------------------|---|

