

Brother HL-L8260CDW színes lézernyomtató



A4, duplex, 2400x600 DPI, USB2.0, LAN, Wi-Fi, 256MB

Cikkszám: HLL8260CDWYJ1

Ár:

199 030 Ft

The HL-L8260CDW provides business quality printing. Built to be truly flexible, the HL-L8260CDW wireless colour printer boasts easy print, and sharing, to deliver productivity seamlessly into your business.

General Specifications

Printer Type

- Laser

Print Method

- Electrophotographic Laser Printer
- (HL-L8260CDW)

Memory Capacity Standard

- 256 MB
- (HL-L8360CDW)
- 512 MB
- (HL-L9310CDW)
- 1 GB

LCD (Liquid Crystal Display)

- (HL-L8260CDW)
- 16 characters x 2 lines
- (HL-L8360CDW/HL-L9310CDW)
- 2.7 in. (67.5 mm) TFT Colour Touchscreen LCD *1

Power Source

- 220 to 240 V AC 50/60 Hz

Peak

- Approximately 1200 W

Printing *2

- Approximately 580 W at 25 °C

Printing

- Approximately 340 W at 25 °C

(Quiet Mode) *2

Ready *2

- Approximately 70 W at 25 °C

Sleep *2

- Approximately 10.0 W

Power Consumption

- (HL-L8260CDW)

(Average)

Approximately 1.2 W

Deep Sleep *2

- (HL-L8360CDW/HL-L9310CDW)

Approximately 1.5 W

Power Off *3 *4		<ul style="list-style-type: none"> (HL-L8260CDW) Approximately 0.02 W (HL-L8360CDW/HL-L9310CDW) Approximately 0.03 W
Dimensions (Typical outline view)		Unit: mm <ul style="list-style-type: none"> (HL-L8260CDW) * : 410 ** : 313 *** : 486 (HL-L8360CDW/HL-L9310CDW) * : 441 ** : 313 *** : 486
Weights (with supplies)		<ul style="list-style-type: none"> (HL-L8260CDW) 21.8 kg (HL-L8360CDW) 21.9 kg (HL-L9310CDW) 22.2 kg
Noise Level	Printing	<ul style="list-style-type: none"> LpAm = 49 dB (A)
	Sound Pressure Printing (Quiet Mode)	<ul style="list-style-type: none"> LpAm = 44 dB (A)
	Ready	<ul style="list-style-type: none"> LpAm = Inaudible
	Monochrome	
	Printing *5 *6	<ul style="list-style-type: none"> LWAd = 6.55 B (A)
	Colour	<ul style="list-style-type: none"> LWAd = 6.56 B (A)
	Sound Power	Monochrome
	Printing (Quiet Mode)	<ul style="list-style-type: none"> LWAd = 6.00 B (A)
	Colour	<ul style="list-style-type: none"> LWAd = 6.00 B (A)
	Ready *5 *6	<ul style="list-style-type: none"> LWAd = Inaudible
Temperature	Operating	<ul style="list-style-type: none"> 10 to 32 °C
	Storage	<ul style="list-style-type: none"> 0 to 40 °C
Humidity	Operating	<ul style="list-style-type: none"> 20 to 80% (without condensation)
	Storage	<ul style="list-style-type: none"> 10 to 90% (without condensation)
Laser Notice		Click here for details.

*1

Measured diagonally

*2

Measured when the machine is connected to the USB interface.

*3

Measured according to IEC 62301 Edition 2.0.

*4

Power consumption varies slightly depending on the usage environment.

*5

Measured in accordance with the method described in RAL-UZ171.

*6

Office equipment with LWAd>6.30 B(A) is not suitable for use in room where people require high levels of concentration. Such equipment should be placed in separate rooms because of noise emissions.

Print Media Specifications

Paper Input	Paper Tray (Standard)	Paper Type	• Plain Paper, Letterhead, Coloured Paper, Thin Paper, Recycled Paper
		Paper Size	• A4, Letter, A5, A5(Long Edge), A6, Executive, Legal, Folio, Mexico Legal
		Paper Weight	• 60 to 105 g/m2
		Maximum Paper Capacity	• Up to 250 sheets of 80 g/m2 Plain Paper
		Paper Type	• Plain Paper, Letterhead, Coloured Paper, Thin Paper, Thick Paper, Thicker Paper, Recycled Paper, Bond, Label, Envelope, Env. Thin, Env.Thick, Glossy Paper
			• Width: 76.2 to 215.9 mm
	Multi-Purpose Tray (MP tray)	Paper Size	• Length: 127 to 355.6 mm
			• Envelope: COM-10, DL, C5, Monarch
		Paper Weight	• 60 to 163 g/m2
	Paper Tray 2, 3, 4 (Optional) *1 *2	Maximum Paper Capacity	• Up to 50 sheets of 80 g/m2 Plain Paper • Envelope: 10 envelopes up to 10 mm thick
		Paper Type	• Plain Paper, Letterhead, Coloured Paper, Thin Paper, Recycled Paper
		Paper Size	• A4, Letter, A5, Executive, Legal, Folio, Mexico Legal
		Paper Weight	• 60 to 105 g/m2 • LT-330CL
		Maximum Paper Capacity	Up to 250 sheets of 80 g/m2 Plain Paper • LT-340CL *3 Up to 500 sheets of 80 g/m2 Plain Paper
			• Up to 150 Sheets of 80 g/m2 Plain Paper (face down delivery to the face down output paper tray)
Paper Output *4	Face Down Output Tray		
	Face Up Output Tray		• One sheet (face up delivery to the face up output tray)
	Automatic 2-sided Printing	Paper Type	• Plain Paper, Letterhead, Coloured Paper, Thin Paper, Recycled Paper, Glossy Paper
		Paper Size	• A4
2-sided		Paper Weight	• 60 to 105 g/m2

*1

(HL-L8260CDW) Maximum number of Lower Trays: Up to three LT-330CL Lower Trays

*2

(HL-L8360CDW/HL-L9310CDW) Maximum number of Lower Trays: Up to three LT-330CL Lower Trays or up to two Lower Trays in any other combinations

*3

Applicable to HL-L8360CDW/HL-L9310CDW

*4

For labels, we recommend removing the printed sheets from the output paper tray immediately after they exit the machine to avoid the possibility of smudging.

Printer Specifications

- | | |
|-------------------------|-------------------------------------------------------------------------------------------------------|
| Automatic 2-sided Print | <ul style="list-style-type: none">• Yes |
| Emulation | <ul style="list-style-type: none">• PCL6, BR-Script3, PDF Version 1.7, XPS Version 1.0 |
| Resolution | <ul style="list-style-type: none">• 600 x 600 dpi, 2,400 dpi class (2400 x 600) quality |

- | | |
|---------------|---------------------------------------------------------------------------------------|
| | Monochrome |
| | <ul style="list-style-type: none">• Up to 33 pages/minute (Letter size) |
| 1-sided print | Up to 31 pages/minute (A4 size) |

- | | |
|-------------------|---------------------------------------------------------------------------------------|
| | Colour |
| | <ul style="list-style-type: none">• Up to 33 pages/minute (Letter size) |
| Print Speed *1 *2 | Up to 31 pages/minute (A4 size) |

- | | |
|---------------|---------------------------------------------------------------------------------------------------------------------|
| | Monochrome |
| | <ul style="list-style-type: none">• Up to 14 sides/minute (Up to 7 sheets/minute) (Letter or A4 size) |
| 2-sided Print | Colour |
| | <ul style="list-style-type: none">• Up to 14 sides/minute (Up to 7 sheets/minute) (Letter or A4 size) |

- | | |
|---------------------|-----------------------------------------------------------------------------------------|
| | Monochrome |
| | <ul style="list-style-type: none">• Less than 15 seconds at 23 °C / 230 V |
| First Print Time *3 | Colour |
| | <ul style="list-style-type: none">• Less than 15 seconds at 23 °C / 230 V |

*1
The print speed may change depending on the type of document you print.

*2
Print speed may be slower when the machine is connected by wireless LAN.

*3
From Ready mode and standard tray

Interface Specifications

- | | |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| USB *1 *2 | <ul style="list-style-type: none">• Hi-Speed USB 2.0 <p>Use a USB 2.0 interface cable that is no more than 2.0 metres long.</p> |
| LAN | <ul style="list-style-type: none">• 10Base-T/100Base-TX/1000Base-T *3 *4 |
| Wireless LAN | <ul style="list-style-type: none">• IEEE 802.11b/g/n (Infrastructure Mode) <p>IEEE 802.11g/n (Wi-Fi Direct®)</p> |
| NFC *5 | <ul style="list-style-type: none">• (HL-L8360CDW/HL-L9310CDW) <p>Yes</p> |

*1
Your machine has a USB 2.0 Hi-Speed interface. The machine can also be connected to a computer that has a USB 1.1 interface.

*2

Third party USB ports are not supported.

*3

Use a straight-through Category 5e (or greater) twisted-pair cable.

*4

When you connect the machine to a Gigabit Ethernet Network, use network devices complying with the 1000BASE-T specification.

*5

When you connect an external IC card reader, use a HID class driver supported device.

Direct Print Feature Specifications

Compatibility	• PDF version 1.7, JPEG, Exif+JPEG, PRN (created by own printer driver), TIFF (scanned by Brother models), XPS version 1.0
Interface	• USB direct interface : Front x 1, Rear x 1 (HL-L9310CDW)

Supported Protocols and Security Features

Ethernet

10Base-T/100Base-TX/1000Base-T

Wireless LAN

IEEE 802.11b/g/n (Infrastructure Mode), IEEE 802.11g/n (Wi-Fi Direct)

Protocols (IPv4)

ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, TFTP client and server, SMTP Client, SNMPv1/v2c/v3, ICMP, Web Services (Print), CIFS client, SNTTP client, LDAP

Protocols (IPv6)

NDP, RA, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, TFTP client and server, SMTP Client, SNMPv1/v2c/v3, ICMPv6, Web Services (Print), CIFS Client, SNTTP Client, LDAP

Network Security (Wired)

SMTP-AUTH, SSL/TLS (IPPS, HTTPS, SMTP), SNMP v3, 802.1x (EAP-MD5, EAP-FAST, PEAP, EAP-TLS, EAP-TTLS), Kerberos, IPsec

Network Security (Wireless)

SMTP-AUTH, SSL/TLS (IPPS, HTTPS, SMTP), SNMP v3, 802.1x (LEAP, EAP-FAST, PEAP, EAP-TLS, EAP-TTLS), Kerberos, IPsec

Wireless Network Security

WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES) *1



Wireless Certification








Wi-Fi Certification Mark License (WPA™/WPA2™ - Enterprise, Personal), Wi-Fi Protected Setup (WPS) Identifier Mark License, Wi-Fi CERTIFIED™ Wi-Fi Direct

*1

Wi-Fi Direct supports WPA2-PSK (AES) only.

Tonerkazetta

	TN-421BK	<ul style="list-style-type: none">• Black• Standard• Approx. 3000 pages in accordance with ISO/IEC 19798	<ul style="list-style-type: none">• How to replace• What is ISO/IEC 19798?
	TN-421C	<ul style="list-style-type: none">• Cyan• Standard• Approx. 1800 pages in accordance with ISO/IEC	<ul style="list-style-type: none">• How to replace• What is ISO/IEC 19798?

		19798	
	TN-421M	<ul style="list-style-type: none"> • Magenta • Standard • Approx. 1800 pages in accordance with ISO/IEC 19798 	<ul style="list-style-type: none"> • How to replace • What is ISO/IEC 19798?
	TN-421Y	<ul style="list-style-type: none"> • Yellow • Standard • Approx. 1800 pages in accordance with ISO/IEC 19798 	<ul style="list-style-type: none"> • How to replace • What is ISO/IEC 19798?
	TN-423BK	<ul style="list-style-type: none"> • Black • High Yield • Approx. 6500 pages in accordance with ISO/IEC 19798 	<ul style="list-style-type: none"> • How to replace • What is ISO/IEC 19798?
	TN-423C	<ul style="list-style-type: none"> • Cyan • High Yield • Approx. 4000 pages in accordance with ISO/IEC 19798 	<ul style="list-style-type: none"> • How to replace • What is ISO/IEC 19798?
	TN-423M	<ul style="list-style-type: none"> • Magenta • High Yield • Approx. 4000 pages in accordance with ISO/IEC 19798 	<ul style="list-style-type: none"> • How to replace • What is ISO/IEC 19798?
	TN-423Y	<ul style="list-style-type: none"> • Yellow • High Yield • Approx. 4000 pages in accordance with ISO/IEC 19798 	<ul style="list-style-type: none"> • How to replace • What is ISO/IEC 19798?

Dobegység



DR-421CL

- Approx. 30000 A4/Letter pages (1 page / job)
- Approx. 50000 A4/Letter pages (3 pages / job)

- How to replace

Hulladékgyűjtő egység



WT-320CL

- Approx. 50000 pages of A4/Letter size paper

- How to replace

Szíjegység



BU-330CL

- Approx. 50000 A4/Letter pages (1 page / job)
- Approx. 130000 A4/Letter pages (3 pages / job)

- How to replace