

TP-Link ES205G Omada switch

LAN (1Gb/s): 5 port, menedzselhető, energiafelhasználás: 3W, szürke

Cikkszám: ES205G

Ár:

17 670 Ft



Garancia: 5 Év

HARDWARE FEATURES

Interface	• 5× 10/100/1000 Mbps RJ45 Ports • AUTO Negotiation/AUTO MDI/MDIX
Fan Quantity	Fanless
Installation	• Desktop • Wall Mount
Physical Security Lock	?
Power Supply	External DC Power Adapter (Output: 5 VDC/ 0.6 A)
Dimensions (W x D x H)	3.9 × 3.9 × 1.0 in (100 × 98 × 25 mm)
Surge Protection	±6kV
PERFORMANCE	
Switching Capacity	10 Gbps
Packet Forwarding Rate	7.4 Mpps
MAC Address Table	8 K
Packet Buffer Memory	4 Mbits
Jumbo Frame	15 KB

SOFTWARE FEATURES

	• Port-based/802.1p/DSCP QoS • 8 Priority Queues • Priority Schedule Mode - WRR (Weighted Round Robin) • Queue Weight Config • Bandwidth Control - Port-Based Rating Limit • Storm Control - Multiple Control Modes (kbps/pps) - Broadcast/Multicast/Unknown-Unicast Control? • Static Link Aggregation • Loop Prevention / Loopback Detection • Flow Control - 802.3x Flow Control • Mirroring - Port Mirroring - One-to-One - Many-to-One - Ingress/Egress/Both • Port Statistics - Port Mirror Status - Traffic Statistics
Quality of Service	
L2 Features	

L2 Multicast	• 802.1ab LLDP • IGMP Snooping
	- IGMP v1/v2/v3 Snooping - Fast Leave
VLAN	• MTU VLAN • Port-Based VLAN
	• 802.1Q Tag VLAN - Max 32 VLAN Groups - 4K VID
Transmission Method	Store-And-Forward
Management Features	
Omada App	Yes. Requires the use of Omada Hardware Controller, Omada Cloud-Based Controller, or Omada Software Controller.
Centralized Management	• Omada Cloud-Based Controller • Omada Hardware Controller • Omada Software Controller
Cloud Access	Yes. Requires the use of Omada Hardware Controller, Omada Cloud-Based Controller, or Omada Software Controller.
Zero-Touch Provisioning	Yes. Requires the use of Omada Cloud-Based Controller
Management Features	• Web-based GUI • DHCP Client • Cable Diagnostics • Automatic Device Discovery[†] • Batch Configuration[†] • Batch Firmware Upgrading[†] • Unified Configuration[†]
OTHERS	
Certification	FCC, CE, RoHS
Package Content	• ES205G • Power Adapter • Installation Guide • Rubber Feet
Environment	• Operating Temperature: 0?~40? (32?~104?) • Storage Temperature: -40?~ 70? (-40?~158?) • Operating Humidity: 10%~90% non-condensing • Storage Humidity: 5%~90% non-condensing

energiafelhasználás	3
LAN (1Gb/s)	5
Gyártó	TP-Link
menedzselhető	Van
szín	szürke