

StarTech PCI-E x1 10/100/1000Mbps SFP hálózati kártya low profile

PCI-E x1: 1db

Cikkszám: PEX1000SFP2

Ár:

135 410 Ft



The PEX1000SFP2 PCI Express Gigabit Fiber Network Card lets you connect a PCI Express-based computer directly to a fiber optic network using the Gigabit SFP of your choice.

This Gigabit fiber card adapts to your network fiber connection and distance requirements to offer flexible configuration via an open SFP slot, and is compatible with most Gigabit SFP transceivers. With broad SFP compatibility the fiber network card lets you use your preferred SFP, giving you more options to connect your computer directly to a fiber network.

With fiber connectivity, your network is not susceptible to electronic interference, often problematic with standard RJ45 copper networks, making this versatile fiber card ideal for secure network setups.

Plus, the card is equipped with a standard profile bracket and includes a low-profile/half-height bracket, perfect for installation in small form-factor computers or 1U server and rackmount applications.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

The StarTech.com Advantage

- Adapts to your network configuration using the fiber transceiver of your choice, through an open SFP slot
- No electronic interference provides a secure fiber network infrastructure through a direct fiber-to-desktop connection
- Fits into full or low-profile/small form factor (SFF) systems, with a dual profile design

Bus Type	PCI Express
Card Type	Standard Profile (LP bracket incl.)
Chipset ID	Realtek - RTL8168E Marvell - 88E1111B1
Industry Standards	IEEE802.3z 1000BASE-SX/LX, IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding, IEEE 802.3x full duplex flow control, RFC 1157 SNMP v1
Interface	Fiber Ethernet
Ports	1
Performance	
Auto MDIX	Yes
Buffer Size	48 KB
Compatible Networks	1000 Mbps (1 Gbps)
Full Duplex Support	Yes
Maximum Data Transfer Rate	2000 Mbps (2 Gbps) - Full-Duplex
Connector(s)	
Connector Type(s)	1 - PCI Express x1 Male
External Ports	1 - SFP Slot Female
Software	

OS Compatibility	Windows® 10 (32/64), 8 / 8.1 (32/64), 7 (32/64), Vista (32/64), XP (32/64) Windows Server® 2012, 2008 R2, 2003 Mac OS® 10.5 and up (Tested up to 10.9) Linux 2.4.x / 2.6.x / 3.5.0 Microsoft Hyper-V®
Special Notes / Requirements	
Note	Fiber data transfer speeds and distances are dependent on the SFP used (sold separately)
System and Cable Requirements	Not compatible with 100Mbps SFP transceivers, Gigabit SFP transceiver required
Indicators	
LED Indicators	1 - Link (Green) 1 - Activity (Yellow)
Power	
Power Consumption	3.2W Max
Environmental	
Humidity	5~95% RH (Non-Condensing)
Operating Temperature	0°C to 45°C (32°F to 113°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Physical Characteristics	
Product Height	4.6 in [118 mm]
Product Length	5 in [128 mm]
Product Weight	2 oz [57 g]
Product Width	0.7 in [18 mm]
Packaging Information	
Shipping (Package) Weight	7.1 oz [200 g]
What's in the Box	
Included in Package	1 - 1 Port PCI Express Gigabit SFP Network Card 1 - Low-Profile Bracket 1 - Driver CD 1 - Instruction Manual