

Asus ProArt PA278QV 27" IPS LED monitor (100% sRGB, 100% Rec. 709) fekete



27", 2560x1440, 16:9, 350cd/m2, 1000:1, 5ms, USB3.0, DVI-D, HDMI, DisplayPort, Mini DisplayPort, fejhallgató kimenet, Line-In, hangszóró, falra szerelhető (VESA), portré mód (pivot), forgatható (swivel), dönthető (tilt), 18,6W

Cikkszám: 90LM05L1-B01370

Ár:

166 570 Ft

Garancia: 3 Év

- Display

Panel Size: Wide Screen 27.0"(68.47cm) 16:9

Color Saturation : 100% sRGB / 100% Rec. 709

Panel Type : IPS

True Resolution : 2560x1440

Display Viewing Area(HxV) : 596.74 x 335.66 mm

Display Surface : Non-glare

Pixel Pitch : 0.2331 mm

Brightness(Max) : 350 cd/?

Contrast Ratio (Max) : 1000:1

ASUS Smart Contrast Ratio (ASCR) : 100000000:1

Viewing Angle (CR?10) : 178°(H)/178°(V)

Response Time : 5ms (Gray to Gray)

Display Colors : 16.7M

Flicker free : Yes

- Video Feature

Trace Free Technology : Yes

ProArt Preset : 9 Modes(sRGB Mode/Rec. 709 Mode/Scenery Mode/Standard Mode/Rapid Rendering/User Mode 1/User Mode 2/Reading Mode/Darkroom Mode)

ProArt Palette : Yes

Color Temperature Selection : 4 Modes

Color Accuracy : ?E< 2

Gamma adjustment : Yes (Support Gamma 1.8/2.0/2.2/2.4/2.6)

Color Adjustment : 6-axis adjustment(R,G,B,C,M,Y)

QuickFit (modes) : Yes (Alignment Grid/Paper/Ruler Modes)

Low Blue Light : Yes

HDCP support : Yes, 1.4

Adaptive-Sync supported : Yes

- Audio Features

Stereo Speakers : 2W x 2 Stereo RMS

- I/O Ports

Signal Input : HDMI(v1.4), Mini DisplayPort 1.2, DisplayPort 1.2, Dual-link DVI-D

PC Audio Input : 3.5mm Mini-Jack

Earphone jack : 3.5mm Mini-Jack

USB Port(s) : 3.0x4

- Signal Frequency

Digital Signal Frequency : 30 ~112 KHz (H) /46 ~75 Hz(V)

- Power Consumption

Power On (Typical): < 18.6W
Power Saving Mode : < 0.5W ;
Power Off Mode : 0W (Hard Switch)
100-240V, 50/60Hz

- Mechanical Design

Chassis Colors : Black

Tilt : +35°~-5°

Swivel : +90°~-90°

Pivot : +90°~-90°

Height Adjustment : 0~150 mm

VESA Wall Mounting : 100x100mm

Frameless Design : Yes

Quick Release Stand Design : Yes

- Security

Kensington lock

- Dimensions

Phys. Dimension with Stand (WxHxD) : 615 x (382 - 532) x 226 mm

Phys. Dimension without Stand (WxHxD) : 615 x 372 x 51 mm

Box Dimension (WxHxD) : 735 x 464 x 216 mm

- Weight

Net Weight (Esti.) : 7.72 kg,

Without Stand (Esti.) : 4.96 Kg,

Gross Weight (Esti.) : 10.77 kg

- Accessories

DVI cable (Optional)

Mini-DisplayPort-to-DisplayPort cable (Optional)

Audio cable(Optional)

Power cord

USB cable(Optional)

Quick start guide

HDMI cable (Optional)

Warranty Card

Color pre-calibration report

Welcome Card

- Compliance and Standards

Energy Star®, BSMI, CB, CCC, CE, CEL level , CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, PSE, RoHS, TUV-Ergo, TUV-GS, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL (Windows 10, Windows 7), RCM, TUV Flicker-free , KC , eStandby, TUV Low Blue Light, TCO, ICES-3, PC recycle

- Note

* Adaptive-Sync only can be activated within “48Hz ~ 75Hz” via HDMI, mini DisplayPort and DisplayPort ports

*To activate Rapid Rendering needs turn off Adaptive-Sync and only be activated at 75Hz. Brightness, Blue Light Filter, ASCR, Trace Free cannot be adjusted when using this function.

*measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection