

TP-Link EAP772-Outdoor BE11000 kültéri Tri-Band Wi-Fi PoE access point



11000Mb/s, IEEE 802.11be (Wi-Fi 7), Bluetooth, LAN (2,5Gb/s): 1 port, antennák száma: 6db, 6dBi, átviteli hatótávolság: 150m, Mesh Wi-Fi, energiafelhasználás: 24,05W, smart home, fehér, IP68

Cikkszám: EAP772-OUTDOOR

Ár:

157 960 Ft

Garancia: 5 Év

HARDWARE FEATURES

Interface	1× 2.5G Ethernet (RJ-45) Port (Support 802.3at PoE)
Button	Reset
Power Supply	• 802.3at PoE
Max. Power	• EU: 21.5W (for PoE)
Consumption	• US: 23W (for PoE)
Dimensions (W x D x H)	9.1× 8.2 × 2.8 in (230 × 207.5 × 69.7 mm)
Antenna	• 2.4 GHz: 2× 4 dBi • 5 GHz: 2× 6 dBi • 6 GHz: 2× 6 dBi L1 (1575.42 MHz) receiver, supporting GPS, Galileo, GLONASS, and BeiDou signals
GNSS	Receive sensitivity: -164dBm (tracking) GPS antennas: Integrated 3dBi omnidirectional antennas
Bluetooth	BLE 5.2
Weatherproof	IP68
Enclosure	
Mounting	Pole/Wall Mounting (Kits included)

WIRELESS FEATURES

Coverage	300m ² (3,200ft ²) Recommended Omnidirectional Coverage
Concurrent Clients	250+ ⁶
Wireless Standards	IEEE 802.11be/ax/ac/n/g/b/a
Frequency	2.4 GHz, 5 GHz, 6 GHz • 802.11be: 8.6 Mbps to 5765 Mbps (MCS0-MCS13, NSS = 1 to 2 HE20/40/80/160/240/320) • 802.11ax: 8.6 Mbps to 2402 Mbps (MCS0-MCS11, NSS = 1 to 2 HE20/40/80/160) • 802.11ac: 6.5 Mbps to 2166.7 Mbps (MCS0-MCS9, NSS = 1 to 2 VHT20/40/80/160) • 802.11n: 6.5 Mbps to 300 Mbps (MCS0-MCS15, HT20/40) • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 4k-QAM • Multiple SSIDs • OFDMA
Signal Rate	

	• Multiple SSIDs (Up to 16 SSIDs, 8 for each band) • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control (Adjust Transmit Power on dBm) • QoS (WMM) • MU-MIMO • MLO • 320MHz • Omada Mesh³ • Seamless Roaming(802.11k/v/r)³ • Band Steering • Load Balance • Airtime Fairness • Beamforming • Rate Limit • Reboot Schedule • Wireless Schedule • Wireless Statistics based on SSID/AP/Client • Static IP/Dynamic IP • Captive Portal Authentication³ • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients
Wireless Functions	
Wireless Security	• SSID to VLAN Mapping • Rogue AP Detection • 802.1X Support • WEP, WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise
Transmission Power	• CE: <20 dBm (2.4 GHz, EIRP), <28 dBm(5 GHz, band 3, EIRP) • FCC: <25 dBm (2.4 GHz), <25 dBm(5 GHz), <25 dBm(6 GHz)
Management Features	
Omada App	Yes
Centralized Management	Yes, through • Omada Cloud-Based Controller • Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller
Cloud Access	Yes, through • Omada Cloud-Based Controller • Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller
Email Alerts	Yes
Management MAC Access Control	Yes
SNMP	v1, v2c
System Logging Local/Remote Syslog	Yes
SSH	Yes
Web-based Management	Yes
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
Zero-Touch Provisioning	Yes. Requiring the use of Omada Cloud-Based Controller
OTHERS	
Certification	CE, FCC, RoHS • Access Point EAP772-Outdoor
Package Content	• Power Cord • Mounting Kits • Installation Guide
System Requirements	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux • Operating Temperature: -30-70 ? (-22-158 ?)

- Environment
- **Storage Temperature: -40-70 ? (-40-158 ?)**

• **Operating Humidity: 10-90% RH non-condensing**

• **Storage Humidity: 5-90% RH non-condensing**

antenna nyeresége	6
cikk kiegészítés	IP68
energiafelhasználás	24.05
LAN (2,5Gb/s)	1
Mesh Wi-Fi	Van
PoE port	1
smart home	Van
Tri-Band	Van
Wi-Fi	Van
Wi-Fi átviteli sebesség	11000
Wi-Fi jeltípus	IEEE 802.11be (Wi-Fi 7)
Wi-Fi titkosítás	WPA3;WPA3-Enterprise;WPA2-PSK;WPA2-Enterprise
Gyártó	TP-Link
antenna típusa	belső
antennák száma	6
átviteli hatótávolság	150
Bluetooth	Van
kültéri	Van
PoE	Van
szín	fehér