

TP-Link InSight S485 smart home kültéri IP kamera IP67



8MP, 2,8mm F1.6 1/2,7" CMOS, Ethernet (100Mb/s), PoE, beépített mikrofon, beépített hangszóró, forgatható, 3840x2160, 25fps, alakfelismerés, mozgásérzékelő, éjszakai mód, microSD, fehér, H.265+;H.264+, 480g

Cikkszám: INSIGHT S485 (2.8MM)

Ár:

143 830 Ft

Garancia: 3 Év

CAMERA

Image Sensor 1/2.7" Progressive Scan CMOS
Shutter Speed 1/3 to 1/10000 s
Slow Shutter Yes
Minimum Illumination 0.005 Lux; 0 Lux with IR/White light
Day/Night Mechanism IR Cut Filter
Day/Night Switch Unified/ Scheduled/ Auto

LENS

Type Fixed Focal Lens
Focal Length 2.8/4 mm
Aperture F1.6
• 2.8 mm:
Horizontal FOV: 111.4°, Vertical FOV: 58.8°, Diagonal FOV: 134°

FOV

• 4 mm:
Horizontal FOV: 91.5°, Vertical FOV: 46.1°, Diagonal FOV: 109.6°

Lens Mount

M12*P 0.5
• 2.8 mm
Detect: 85 m (278 ft)
Observe: 35 m (116 ft)
Recognize: 17 m (56 ft)
Identify: 8 m (28 ft)

DORI Distance

• 4 mm
Detect: 107 m (350 ft)
Observe: 44 m (146 ft)
Recognize: 21 m (70 ft)
Identify: 11 m (35 ft)

Angle Adjustment (Manual)

Range Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°

ILLUMINATOR

IR LED Quantity: 4
Range: 30m
Wavelength: 850nm

White LED Quantity: 4
Range: 30m

Illuminator On/Off Control Auto/Scheduled/Always on/Always off

VIDEO

Max. Resolution 3840 X 2160

- Frame Rate:
50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps

Main Stream

- Resolution:
3840x2160, 2560x1440, 2304x1296, 2048x1280, 1920x1080, 1280x720

- Note:
If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
If 120dB is turned on, the frame rate can only support up to 20fps.

- Frame Rate:
50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps

Sub-Stream

- Resolution:
848x480, 704x576, 640x480, 640x360, 352x288, 320x240

- Note:
If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
If 120dB is turned on, the frame rate can only support up to 20fps.

Bit Rate Control

CBR, VBR

Video Compression

Main Stream: H.265+/H.265/H.264+/H.264

Sub-Stream: H.265/H.264

H.264 Type

High Profile

H.264+

Main Stream Supported

H.265 Type

Main Profile*

H.265+

Main Stream Supported*

Video Bit Rate

Main Stream: 256 Kbps to 8 Mbps

Sub-Stream: 64 Kbps to 512 Kbps

Image

- Mirror
- Brightness
- Contrast
- Saturation
- Sharpness
- Exposure
- WDR
- White Balance
- Prevent Overexposure to Infrared Light
- HLC Adjustable by Client Software

Image Settings

Image Enhancement

BLC/3D DNR/HLC/SmartIR
120 dB

Wide Dynamic Range

Note: When People & Vehicle Analytics is enabled, only DWDR is supported.

SNR

? 52 dB

Image Parameters Switch

Yes

Privacy Mask

Up to 4 Masks

ROI

1 Region

OSD Setting

Yes

AUDIO

Audio Communication

Two-Way Audio

Audio Input

Yes

Audio Output

Yes

Audio Compression

Yes

Audio Sampling Rate

8KHz

Environment Noise Filtering

Yes

Audio Bit Rate

64 Kbps(G.711 alaw)

NETWORK

Protocol

TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP

ONVIF

Yes

API	ONVIF Profile S/T/G
Simultaneous Live View	3 Main Streams & 3 Sub-Streams
Client	VIGI App, VIGI Security Manager, Web UI, VIGI VMS, VIGI Cloud VMS
Web Browser	Google Chrome® 57 and above
	Firefox® 52 and above
	Safari® 11 and above
	Microsoft® Edge 91 and above
Cloud	Yes
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
ALARM AND EVENT MANAGEMENT	
Smart Event	• Intrusion Detection
	• Line-Crossing Detection
	• Region Entering Detection
	• Region Exiting Detection
	• Object Abandoned Detection
	• Object Removal Detection
	• Loitering Detection
	• People Detection
	• Vehicle Detection
	• Abnormal Sound Detection
	• Scene Change Detection
	• Motion Detection (Enhanced with Human & Vehicle Classification for more accurate alerts)
	• Video Tampering Detection
Basic Event	• Exception (Illegal Login)
	• Memory Card Video Recording
	• Message Push
Alarm Linkage	• Audible Warning
	• White Light Flashing
Linkage Method	N/A
Output Notification	Message Push
Deep Learning Function	
People & Vehicle Analytics	Search and filter to people or vehicle of interest based on many different attributes, making post-event search faster and easier. [§]
INTERFACES	
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE
Alarm	N/A
Reset Button	Yes
Power	DC Power Port
On-board Storage	Built-In Memory Card Slot, Support MicroSD Card, up to 512 GB**
Built-in Microphone	Yes; Records Anything Going on within a 15-ft Radius of the Camera
Built-in Speaker	Yes
Audio	N/A
GENERAL	
Operating Temperature	-30-60 °C
Storage Temperature	-40-60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing)
Package Contents	VIGI Network Camera
	Quick Start Guide
	Waterproof Cable Attachments
	Mounting Accessories
Material	Metal
Net Weight	0.48 Kg
Power Supply	12V DC ± 5%, Max. 11.5 W, 5.5 mm Coaxial Power Plug
	PoE: 802.3af/at, class 0, Max. 12.5 W
Protection	IP67
Product Dimensions (L x W x H)	4.4 × 4.4 × 3.3 in (111 × 111 × 83.7 mm)
Certifications	CE, NTRA, VCCI, KC, BSMI, FCC, IC

alakfelismerés	Van
beépített hangszóró	mono
érzékelő felbontása	8MP
látószög	134°
smart home	Van
tömeg	480
videó felbontása	3840x2160
Gyártó	TP-Link
beépített mikrofon	Van
cikknév kiegészítés	IP67
csatlakozó	Ethernet (100Mb/s)
döntési szög	75
éjszakai mód	Van
érzékelő típusa	2,8mm F1.6 1/2,7" CMOS
forgatási szög	360
forgatható	Van
kamera rögzítés típusa	mennyezetre rögzíthető
memóriakártya foglalat	microSD
mozgásérzékelő	Van
PoE	Van
rögzítési formátumok	H.265+;H.264+
rögzítési sebesség	25
szín	fehér