

Huawei eKit Switch S110-8P2ST PoE switch

LAN (1Gb/s): 9 port, SFP: 1db, szürke

Cikkszám: 98012269

Ár:

66 370 Ft



Garancia: 3 Év	
Integrated fixed deviceY	
Dimensions without packaging (H x W x D)	Basic dimensions (excluding the parts protruding from the body): 35 mm x 210.0 mm x 130.0 mm (1.38 in. x 8.27 in. x 5.12 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 36.5 mm x 210.0 mm x 131.7 mm (1.44 in. x 8.27 in. x 5.19 in.)
Dimensions with packaging (H x W x D)	150.0 mm x 270.0 mm x 200.0 mm (5.91 in. x 10.63 in. x 7.87 in.)
Chassis height	0.8
Installation type	Desk mounting,Wall mounting
Weight without packaging	1.11 (2.45)
Weight with packaging	1.46 (3.22)
Typical power consumption	11
Typical heat dissipation	37.53
Maximum power consumption	Without PoE: 11 W Full PoE load: 155 W (PoE: 124 W)
Maximum heat dissipation	- Without PoE: 37.53 - Full PoE load: 528.88
Static power consumption	3
100% power consumption	11
MTBF	78.77
MTTR	2
Availability	>0.99999
Noise at normal temperature (acoustic Noise-free (no fans), < 30 power)	
Noise at high temperature (acoustic Noise-free (no fans), < 30 power)	
Noise at normal temperature (acoustic Noise-free (no fans), < 20 pressure)	
Number of card slots	0
Number of power slots	0
Number of fans	

number of fans	0
modules	
Maximum number of physical ports on the entire device	10
Maximum number of 100GE ports	0
Maximum number of 40GE ports	0
Maximum number of 25GE ports	0
Maximum number of 10GE ports	0
Maximum number of 5GE ports	0
Maximum number of 2.5GE ports	0
Maximum number of GE ports	10
Maximum number of FE ports	10
Dedicated stack port	Not supported
Redundant power supply	Not supported
Long-term operating temperature	0°C to 40°C (32°F to 104°F) at an altitude of 0-1800 m (0-5906 ft.)
Restriction on the operating temperature variation rate	When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.).
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity	5% RH to 95% RH (non-condensing)
Long-term operating altitude	0-5000 m (0-16404 ft.)
Storage altitude	0-5000 m (0-16404 ft.)
Power supply mode	Power adapter
Rated input voltage	Power adapter input: 170-240 V AC; 50/60 Hz Power adapter output: 56 V DC
Input voltage range	Power adapter input: 170-264 V AC; 47-63 Hz
Maximum input current	2.68 A
CPU	-
Memory	-
Flash memory	-
Console port	Not supported
Eth Management port	Not supported
USB	Not supported
Hardware real-time power detection	Not supported
Dying gasp	Not supported
RTC	Not supported
RPS input	Not supported
Complete device sleeping	Not supported
Service port surge protection	Common mode: ±4 kV
Power supply surge protection	Differential mode: ±6 kV; common mode: ±6 kV
Ingress protection level	IP20
(dustproof/waterproof)	
Types of fans	None
Heat dissipation mode	Natural heat dissipation

Airflow direction	-
PoE	Supported
Maximum PoE power consumption	124
PoE+ power interfaces	8
PoE++ power interfaces	-
Full load PoE power consumption 15.4W (802.3af)	8
Full load PoE power consumption 30W (802.3at)	4
Full load PoE++ power consumption 60W (802.3bt)	-
Full load PoE++ power consumption 90W (802.3bt)	-
Certification	EMC certification Safety certification Manufacturing certification

---

GyártóHuawei