

# StarTech Dual DVI USB +Audio & USB 2.0 Hub

USB2.0 bemenet: 4db, USB2.0 kimenet: 4db

Cikkszám: SV431DD2DUA

Ár:

188 520 Ft



The SV431DD2DUA 4-port Dual DVI USB KVM Switch allows up to four PCs, each with dual DVI video outputs, to share two monitors, one microphone and set of speakers, one keyboard and one mouse as well as two other USB peripherals.

An ideal solution for graphic designers, CAD/CAM designers or educational and financial institutions, the dual view KVM Switch allows you to instantly switch back and forth between dual DVI display PCs at the touch of a button, while maintaining professional level video quality on both monitors. The dual DVI switch also features an integrated USB hub port that allows USB 2.0 peripherals such as thumb drives, external hard drives or web cams to be shared between attached systems - eliminating duplicate peripheral costs.

Please Note: While both DVI-I (analog mode) and DVI-D (digital only) are supported by the KVM, both source PCs should output the same signal type for proper switching. It is recommended wherever possible to use DVI-D cables across all PC to KVM and KVM to Console connections. Please contact technical support if you require assistance identifying your source.

Backed by a StarTech.com 3 year warranty and free lifetime technical support.

The StarTech.com Advantage

- Integrated USB 2.0 hub and Mic/Audio ports allow the user to have full multimedia control of two computers and share USB peripherals eliminating the expense of duplicate devices
- Take full advantage of Dual head video cards by switching up to four machines across two high resolution DVI monitors
- Absolutely no software or drivers required providing a completely OS independent KVM solution

### Hardware

Audio	Yes
Cables Included	No
Daisy-Chain	No
KVM Ports	4
Multi-Monitor	Yes
PC Interface	USB
PC Video Type	DVI
Rack-Mountable	Optional

### Performance

DVI Support	Yes - Single Link
Hot-Key Selection	Yes
IP Control	No
Maximum Analog Resolutions	2048x1536 @85Hz
Maximum Digital Resolutions	1920x1200 @60Hz
Maximum Number of Users	1
Port Selection Support	Push Button and Hotkeys

### Connector(s)

Console Interface(s)	2 - 3.5 mm Mini-Jack (3 Position) Female
	2 - DVI-I (29 pin) Female
	4 - USB A (4 pin) Female
Host Connectors	4 - USB B (4 pin) Female
	8 - 3.5 mm Mini-Jack (3 Position) Female
	8 - DVI-I (29 pin) Female
<b>Software</b>	
OS Compatibility	OS independent; No software or drivers required
<b>Indicators</b>	
LED Indicators	1 - Green - Power
	4 - Green - Host Online, Red - Host Selected
<b>Power</b>	
Center Tip Polarity	Positive
Input Current	0.8A
Input Voltage	110 ~ 240 AC
Output Current	1.5A
Output Voltage	12 DC
Plug Type	M
Power Source	AC Adapter Included
<b>Environmental</b>	
Humidity	90% RH
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
<b>Physical Characteristics</b>	
Color	Black
Enclosure Type	Steel
Product Depth	5.1 in [130 mm]
Product Height	2.4 in [60 mm]
Product Weight	44.2 oz [1253 g]
Product Width	8.7 in [220 mm]
<b>Packaging Information</b>	
Shipping (Package) Weight	4 lb [1.8 kg]
<b>What's in the Box</b>	
Included in Package	1 - 4 Port Dual DVI USB KVM
	4 - Rubber Feet
	1 - Universal Power Adapter (US/EU/UK) and AU in Australia
	1 - Instruction Manual