

## Asus DSL-AC88U AC3100 Dual-Band Wi-Fi VDSL/ADSL2+ modem/router

WAN (1Gb/s): 1 port, LAN (1Gb/s): 4 port, USB2.0, USB3.0, RJ11: 1db, 3167Mb/s, IEEE 802.11a/b/g/n/ac (Wi-Fi 5), antennák száma: 4db, fekete, Annex B

Cikkszám: 90IG02W1-BN3G10

Ár:

**168 400 Ft**



Garancia: 3 Év

- Network Standard  
IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, IPv4, IPv6
- Product Segment  
AC3100 ultimate AC performance : 1000+2167 Mbps
- Wi-Fi Data Rate  
802.11a : 6,9,12,18,24,36,48,54 Mbps  
802.11b : 1, 2, 5.5, 11 Mbps  
802.11g : 6,9,12,18,24,36,48,54 Mbps  
802.11n : up to 600 Mbps  
802.11n TurboQAM : up to 800 Mbps  
802.11ac : up to 1734 Mbps  
1024QAM (2.4GHz) : up to 1000 Mbps  
1024QAM (5GHz) : up to 2167 Mbps
- xDSL Data Rate  
G.fast Upstream: 500Mbps, Downstream: 900Mbps  
VDSL2 profile 35b Upstream: 100Mbps, Downstream: 300Mbps  
VDSL2 profile 30a Upstream: 100Mbps, Downstream: 200Mbps  
VDSL profile 17a Upstream: 50Mbps, Downstream: 100Mbps  
VDSL profile 12a, 12b Upstream: 22Mbps, Downstream: 68Mbps  
VDSL profile 8a, 8b, 8c, 8d Upstream: 16Mbps, Downstream: 50Mbps  
ADSL2 Upstream: 3.3Mbps, Downstream: 24Mbps  
ADSL2 Upstream: 3.5Mbps, Downstream: 12Mbps
- Features  
?DHCP server, firewall/NAT, DynDNS  
?VPN server(PPTP/Open VPN)  
?VPN client(PPTP/L2TP/Open VPN)  
?Dual WAN Fail over/Fail back  
?Quality of Service (QoS)  
?IPTV(VDSL/ADSL WAN)  
?DSL feedback mechanism  
?Save/Restore configuration file
- Antenna  
Detachable dBi antenna x 4
- LED Indicator  
Power, VDSL, Internet, LAN x 2, 5 GHz Wi-Fi, 2.4 GHz Wi-Fi, USB x 1, E-WAN
- Button  
WPS Button, Reset Button, Power Button, Wireless on/off Button, LED on/off Button
- Ports

- 1 x RJ11 for xDSL
- 4 x RJ45 10/100/1000/Gigabits BaseT for LAN
- 1 x RJ45 10/100/1000/Gigabits BaseT for WAN
- USB Ports
  - USB 2.0 x 1
  - USB 3.0 x 1
- USB Applications
  - Printer Server
  - FTP Server
  - Download Master
  - 3G/4G sharing
- Operating Frequency
  - 2.4GHz
  - 5GHz
- Operation Channel
  - 13 Europe (ETSI)
- Security
  - WPA2-PSK, WPA-PSK
- Management
  - Web-based GUI configuration
  - Firmware upgraded, configuration data uploaded and downloaded via Web-based GUI
  - Auto VPI/VCI detection
  - Configuration backup and restore
- VPN Support
  - PPTP Pass-Through
  - OpenVPN server
  - PPTP client
  - L2TP client
  - OpenVPN client
- Power Adapter
  - AC Input : 110 ~240 V(50~60HZ)
  - DC Output : 19 V/3.42 A
- Dimensions
  - 292 x 180 x 61 ~ mm (WxDxH) (Without Bezel)
- Weight
  - 795 g (Device Only)
- OS Support
  - Windows® 10
  - Windows® 8.1
  - Windows® 8
  - Windows® 7
  - Windows® XP
  - Mac OS X
- Package Content
  - VDSL/ADSL DSL-AC88U
  - Network cable (RJ-45)
  - Power adapter
  - Splitter
  - DSL Cable
  - Warranty card
  - Quick Start Guide
  - Support CD