

TP-Link RE500X AX1500 Dual-Band Wi-Fi range extender



1500Mb/s, IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), LAN (1Gb/s): 1 port,
antennák száma: 2db, Mesh Wi-Fi, energiafelhasználás: 10W, fehér

Cikkszám: RE500X

Ár:

29 120 Ft

Garancia: 3 Év

- Ports1 Gigabit Ethernet Port
- ButtonWPS Button, Reset Button
- Power Consumption10W
- Dimensions (W x D x H)3.1×1.4×5.9 in. (78×36×149 mm)
- Antenna2 Internal Antennas

WIRELESS FEATURES

- Wireless StandardsIEEE 802.11a/n/ac/ax 5GHz, IEEE 802.11b/g/n 2.4GHz
- Frequency2.4GHz and 5GHz
- Signal Rate300 Mbps at 2.4GHz, 1200 Mbps at 5GHz

Reception Sensitivity

- 11a 6Mbps: -93dBm,
- 11a 54Mbps: -75dBm
- 11ac HT20 MCS0: -92dBm,
- 11ac HT20 MCS8: -70dBm
- 11ac HT40 MCS0: -90dBm,
- 11ac HT40 MCS9: -66dBm
- 11ac HT80 MCS0: -87dBm,
- 11ac HT80 MCS9: -62dBm

2.4GHz:

- 11g 54Mbps: -77dBm,
- 11n HT20 MCS7: -75dBm
- 11n HT40 MCS7: -72dBm

- Transmit PowerCE: 2.4GHz ≤20dBm, 5GHz ≤30dBm
- Wireless FunctionsEnable/Disable Wireless Radio, Wireless Statistics
- Wireless Security64/128-bit WEP, WPA/WPA-PSK2 encryptions

OTHERS

- Package ContentsWi-Fi Range Extender RE500X
Quick Installation Guide
- System RequirementsMicrosoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux
Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser
- CertificationsFCC, RoHS

