

Delock HDMI -> HDMI Jack stereo 3,5mm Toslink standard RCA Female audio extractor

Cikkszám: 62692

Ár:

26 730 Ft



This adapter can be used to extract the audio signal from an HDMI transmission. While the image signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) and analog (stereo) to other devices such as headphones or a surround receiver.

Specification

- Connector:
 - Input:
 - 1 x HDMI A 19 pin female
 - 1 x DC Power 5 V
 - Output:
 - 1 x HDMI A 19 pin female
 - 1 x 3.5 mm 3 pin Stereo jack female (Stereo Audio)
 - 1 x TOSLINK (S/PDIF)
 - 1 x RCA (S/PDIF)
- Switchable between stereo (2.0) and surround (5.1)
- Compatible with High Speed HDMI, 3D and HDCP 1.4
- Output with HDMI repeater function
- Resolution up to 3840 x 2160 @ 30 Hz (8-bit), 1920 x 1080 @ 60 Hz (12-bit)
- Video bandwidth up to 300 MHz / 3 Gb/s per channel, 9 Gb/s max.
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz (depending on the system and the connected devices)
- CEC and HDMI audio routed to the output (pass-through)
- Audio DAC CS4344, 24 bit / 192 kHz
- Robust metal housing
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): 71 x 61 x 21 mm
- Length: power cable USB Type-A > DC ca. 50 cm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
 - inside: Ø ca. 2.1 mm
 - outside: Ø ca. 5.5 mm
 - length: ca. 9 mm

System requirements

- A free HDMI A female port

Package content

- HDMI Audio Extractor
- Mounting brackets and screws
- USB power cable
- Power supply 5 V
- User manual

Package

- Box

Gyártó	Delock
2. kimeneti csatlakozó	Jack stereo 3,5mm
3. kimeneti csatlakozó	Toslink Standard
4. kimeneti csatlakozó	RCA
bemeneti csatlakozó	HDMI
csatlakozó típus	Female
irány	->
kimeneti csatlakozó	HDMI