

Delock M.2 SATA beépítő keret

beépítési méret: 2,5", SATA

Cikkszám: 62704

Ár:

57 140 Ft

M.2 NVMe



This Delock converter enables the connection of a M.2 NGFF SSD in 2280, 2260, 2242 and 2230 format with key B and a M.2 NGFF SSD in 2280, 2260, 2242 and 2230 format with key M. It allows the possibility to connect a M.2 SSD based on PCIe and M.2 SSD based on SATA at the same time. The converter can be installed into your system internally through the SATA 22 pin interface while using a SATA M.2 SSD, or via the SFF-8643 interface while using a PCIe M.2 SSD.

Specification

- Connector:
 - 1 x SATA 6 Gb/s 22 pin female (for SATA SSDs)
 - 1 x 36 pin SFF-8643 female (for PCIe SSDs 2 or 4 lanes)
 - 1 x 67 pin M.2 NGFF key M slot (PCIe SSD)
 - 1 x 67 pin M.2 NGFF key B slot (SATA SSD)
- Interface: SATA / PCIe (2 or 4 lanes)
- Supports M.2 NGFF modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe or SATA
- Maximum height of the components on the module: 1.5 mm application of double-sided assembled modules supported
- SATA 15 pin power connector always necessary
- LEDs for power and activity
- Supports NVM Express (NVMe)
- Maximum output current: 4 A (PCIe) and 3 A (SATA)

System requirements

- Windows 7/7-64/8/8-64/8.1/8.1-64/10/10-64, Linux Kernel 3.16
- A free SATA 22 pin interface
- A free SFF-8643 interface (PCIe SSD)

Package content

- 3.5" converter
- 2 x fixing screw for M.2 module

Package

- Box

meghajtó méret	M.2
Gyártó	Delock
beépítési méret	2,5"

elfoglalt egységek száma	1
irány	->
SATA	1