

FSP Champ 3000VA tower szünetmentes tápegység



3000VA, 2700W, LCD, menedzselhető, USB2.0, soros port

Cikkszám: CHAMP 3K TOWER

Ár:

221 590 Ft

SOS UPS forródrót : Telefon : +36 1 236-3060 Fax : +36 1 349-6721 Email : sosups@sosups.hu Képzett mérnökök segítenek az FSP UPS üzemeltetésével kapcsolatos problémák megoldásában. A garanciális ügyintézés továbbra is nálunk történik.

FSP Champ is the high density version of double-conversion online UPS with a output power factor 0.9. It's designed in small cabinet with microprocessor controller. Champ also have USB and RS-232 communication ports as standard, with a built-in intelligent slot for additional adapters, protocol converters and relate contact cards.

Features:

- True double-conversion
- Microprocessor control optimizes reliability
- Input power factor correction
- Output power factor 0.9
- Wide input voltage (120 V – 300 V)
- Converter mode available
- ECO mode for energy saving
- Generator compatible
- Charger capacity expansion to 6A for long-run models
- Smart SNMP works well with either USB or RS-232 together
- Comprehensive display allows easy monitoring and access of UPS status

Specifications:

Model	Champ TW 1K(L)	Champ TW 2K(L)	Champ TW 3K(L)
Capacity	1000 VA / 900W	2000 VA / 1800W	3000 VA / 2700W
Input Voltage Range	120-300 VAC $\pm 5\%$		
Input Frequency	40Hz ~ 70Hz		
Power Factor	≥ 0.99 @ Nominal Voltage (100% load)		
Output Voltage	$\pm 1\%$ (Batt. Mode)		
Output Frequency Range	47.5 Hz ~ 52.5 Hz or 57Hz ~ 63 Hz (Synchronized Range) 50 Hz ± 0.25 Hz or 60 Hz ± 0.3 Hz (Batt. Mode)		
Current Crest Ratio	3:1		
Harmonic Distortion	$\leq 3\%$ THD (Linear Load) $\leq 6\%$ THD (Non-linear Load)		
Output Transfer Time (Typical)	Zero (AC to DC) 4ms (Inverter to Bypass)		
Output Waveform (Batt. Mode)	Pure Sinewave		
Battery Type & Number	12V / 9Ah x 2	12V / 9Ah x 4	12V / 9Ah x 6
Backup Time (One PC load@120W)	N/A		
Typical Recharge Time (up to 90%)			

Typical Recharge Time (up to 90 % capacity)	4 hours		
Indicators / AC Mode			
Indicators / Battery Mode			
Indicators / Battery level			
Indicators / Load level			
Indicators / Bypass mode			
Indicators / Fault			
Alarm / Battery Mode	Sounding every 4 seconds		
Alarm / Low Battery	Sounding every second (Batt. Mode)		
Alarm / Overload	Sounding twice per second		
Alarm / Fault	Continuously sounding		
Physical Dimension (mm)	282 x 145 x 220	397 x 145 x 220	421 x 190 x 318
Physical Net Weight (kg)	9.8	17	27.6
Standard Model			
Physical Net Weight (kg)	4.1	6.8	7.4
Long-run Model			
Operating Environment / Humidity	20-90 % RH @ 0- 40°C (non-condensing)		
Operating Environment / Noise Level	Less than 50dB @ 1 Meter		
Management / Optional USB / RS-232 Port	Supports Windows® 98/2000/2003/XP/Vista/2008, Windows® 7/8, Linux, and MAC		
Optional SNMP	Power management from SNMP manager and web browser		

kimenő hálózati C13 aljzat	4
látszólagos teljesítmény	3000
topológia	online
Gyártó	FSP
akkumulátor típusa	12V/9AH
akkumulátorok száma	6
frekvencia tartomány	40/70Hz
hullámforma típus	tiszta szinuszhullám
kapacitás	3000
menedzselhető	Van
riasztási funkció	Van
RJ11	Nincs
soros port	1
széria	Champ
teljesítmény	2700
tipikus újratöltési idő	4
tömeg	27.6 kg
USB2.0	Van
visszajelzés	LCD
magasság	421 mm

mélység	318 mm
szélesség	190 mm
szín	fekete