

StarTech PCI 4 portos USB3.0 IO vezérlő

illesztés: PCI, USB3.0: 4db, low profile, PCI: 1db

Cikkszám: PCIUSB3S4

Ár:

50 320 Ft



The PCIUSB3S4 4-Port PCI to USB 3.0 Card enables legacy PCI slots to support the SuperSpeed USB 3.0 standard, which is capable of data transfer rates up to 5 Gbps. Using USB 3.0 devices with this card will increase data transfer rates with up to 1.3 Gbps of available bandwidth (PCI bus limit) - more than doubling performance compared to a USB 2.0 connection.

This versatile USB 3.0 adapter includes an optional SATA power connector which allows each USB port to deliver up to 900mA of power to connected USB 3.0 devices - suitable for even the most power hungry devices.

A perfect solution for older PCI-based systems or computers with only PCI expansion slots remaining, the card allows those systems to stay relevant and up-to-date with the latest USB technology. The card is also backward compatible with USB 2.0 and 1.x devices, so it will not only work with any future USB 3.0 devices, but will also support older devices.

The PCIUSB3S4 4-Port PCI USB 3.0 Card is backed by StarTech.com lifetime warranty and free lifetime technical support.

The StarTech.com Advantage

- Increased data transfer rates (up to 1.3 Gbps PCI bus limit) with USB 3.0 compatible devices
- Suitable for installation in standard-sized and Small Form Factor computers
- Supports bus-powered USB 3.0 devices

Bus Type	PCI / PCI-X (5 / 3.3V)
Card Type	Standard Profile (LP bracket incl.)
Chipset ID	NEC uPD720202
Interface	USB 3.0
Ports	4
Performance	
Maximum Data Transfer Rate	1.3 Gbps (PCI Bus)
Type and Rate	USB 3.0 - 5 Gbit/s
UASP Support	Yes
Connector(s)	
Connector Type(s)	1 - PCI / PCI-X (Universal 3.3 & 5V; 32-bit)
External Ports	4 - USB 3.0 A (9 pin; SuperSpeed) Female
Internal Ports	1 - SATA Power (15 pin) Plug 1 - SP4 (4 pin; Small Drive Power) Plug

Software

OS Compatibility	Windows® 10 (32/64), 8 / 8.1 (32/64), 7 (32/64), Vista (32/64), XP (32/64) Windows Server® 2012, 2008 R2, 2003
------------------	---

Special Notes / Requirements

System and Cable Requirements	Available PCI slot Available SATA or Floppy power connector
-------------------------------	--

Environmental

Humidity	15% ~ 90% RH
Operating Temperature	5°C to 50°C (41°F to 122°F)

Storage Temperature -25°C to 70°C (13°F to 158°F)

Physical Characteristics

Color Red
Product Height 2.6 in [65 mm]
Product Length 5.2 in [133 mm]
Product Weight 2.8 oz [80 g]
Product Width 0.8 in [20 mm]

Packaging Information

Shipping (Package) Weight 0.5 lb [0.2 kg]

What's in the Box

Included in Package
1 - PCI USB 3.0 Card
1 - Low Profile Bracket
1 - Driver CD
1 - Instruction Manual