

TP-Link EAP230-WALL Omada AC1200 Dual-Band Wi-Fi PoE
access point



1200Mb/s, IEEE 802.11a/b/g/n/ac (Wi-Fi 5), LAN (1Gb/s): 2 port, antennák száma: 2db, energiafelhasználás: 7W, fehér

Cikkszám: EAP230-WALL

Ár:

43 390 Ft

Garancia: 5 Év

Interface Uplink: 10/100/1000 Mbps Ethernet Port*1
Downlink: 10/100/1000 Mbps Ethernet Port*1

Physical Security LockNo

Button LED/Wi-Fi Button, RESET

Power Supply 802.3af/802.3at PoE

Power Consumption 7 W

Dimensions 3.4 × 3.4 × 1.2 in (86.8 × 86.8 × 30.2 mm)
2 Dual-Band Antennas

Antenna 2.4GHz: 2*4 dBi
5GHz: 2*3.6 dBi

Mounting Wall Plate Mounting

Hardware Watch Dog Yes

WIRELESS FEATURES

Wireless Standards IEEE 802.11n/g/b/ac

Frequency 2.4GHz and 5GHz

Signal Rate 5GHz: Up to 867Mbps
2.4GHz: Up to 300Mbps
16 SSIDs(Up to 8 SSIDs on each band)
Enable/Disable Wireless Radio
Automatic Channel Assignment
Transmit Power Control (Adjust Transmit Power on dBm)
QoS(WMM)
Load Balance

Wireless Functions Rate Limit
Reboot Schedule
Wireless Schedule
Wireless Statistics based on SSID/AP/Client
MU-MIMO
Band Steering
Beamforming
Captive Portal Authentication
Access Control
Wireless Mac Address Filtering
Wireless Isolation Between Clients
Wireless Security SSID to VLAN Mapping
Local LAN port based VLAN
Rogue AP Detection
802.1X Support

64/128/152-bit WEP / WPA / WPA2-Enterprise,
WPA-PSK / WPA2-PSK
CE:

Transmission Power ≤20 dBm (2.4 GHz, EIRP)
≤23 dBm (5 GHz, EIRP)

MANAGEMENT

Omada Cloud Access Yes

Omada App Yes

Omada Cloud Controller Yes

Centralized Management

- Omada Cloud-Based Controller
- Omada Hardware Controller (OC300)
- Omada Hardware Controller (OC200)
- Omada Software Controller

Omada Controller Software Yes

Cloud Access Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)

Email Alerts Yes

LED ON/OFF Control Yes

Management MAC Access Yes

Control

SNMP v1,v2c

System Logging Local/Remote Local/Remote Syslog

Syslog

SSH Yes

Web-based Management HTTP/HTTPS

L3 Management Yes

Multi-site Management Yes

Management VLAN Yes

OTHERS

Certification CE, RoHS
Omada AC1200 Wireless MU-MIMO Gigabit Wall-Plate Access Point

Package Contents EAP230-Wall
Installation Guide
Mounting Screw

System Requirements Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10

Operating Temperature: 0-40 ° (32-104 °)

Storage Temperature: -40-70 ° (-40-158 °)

Operating Humidity: 10-90% non-condensing

Storage Humidity: 5-90% non-condensing

Dual-Band	Van
energiafelhasználás	7
LAN (1Gb/s)	2
PoE port	1
Wi-Fi átviteli sebesség	1200
Wi-Fi jeltípus	IEEE 802.11a/b/g/n/ac (Wi-Fi 5)
Wi-Fi titkosítás	64/128/152-bit WEP;WPA2-PSK;WPA2-Enterprise
Gyártó	TP-Link
antenna típusa	belső
antennák száma	2
PoE	Van

WI-FI

Van

szín

fehér